

SN54HC14, SN74HC14 HEX SCHMITT-TRIGGER INVERTERS

D2684, DECEMBER 1982—REVISED SEPTEMBER 1987

- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

description


These Schmitt-trigger devices contain six independent inverters. They perform the Boolean function $Y = \bar{A}$.

The SN54HC14 is characterized for operation over the full military temperature range of -55°C to 125°C . The SN74HC14 is characterized for operation from -40°C to 85°C .

FUNCTION TABLE
(each inverter)


INPUT A	OUTPUT Y
H	L
L	H

logic symbol†




† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.
Pin numbers shown are for D, J, and N packages.


logic diagram (positive logic)



SN54HC14 . . . J PACKAGE
SN74HC14 . . . D OR N PACKAGE
(TOP VIEW)



SN54HC14 . . . FK PACKAGE
(TOP VIEW)



NC—No internal connection

2

HCMOS Devices

PRODUCTION DATA documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS
INSTRUMENTS**

POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

Copyright © 1982, Texas Instruments Incorporated

2-57

SN54HC14, SN74HC14
HEX SCHMITT-TRIGGER INVERTERS

absolute maximum ratings over operating free-air temperature†

Supply voltage, V_{CC}	-0.5 V to 7 V
Input clamp current, I_{IK} ($V_I < 0$ or $V_I > V_{CC}$)	± 20 mA
Output clamp current, I_{OK} ($V_O < 0$ or $V_O > V_{CC}$)	± 20 mA
Continuous output current, I_O ($V_O = 0$ to V_{CC})	± 25 mA
Continuous current through V_{CC} or GND pins	± 50 mA
Lead temperature 1,6 mm (1/16 in) from case for 60 s: FK or J package	300°C
Lead temperature 1,6 mm (1/16 in) from case for 10 s: D or N package	260°C
Storage temperature range	-65°C to 150°C

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

recommended operating conditions

		SN54HC14			SN74HC14			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC} Supply voltage		2	5	6	2	5	6	V
V_{IH} High-level input voltage	$V_{CC} = 2$ V	1.5			1.5			V
	$V_{CC} = 4.5$ V	3.15			3.15			
	$V_{CC} = 6$ V	4.2			4.2			
V_{IL} Low-level input voltage	$V_{CC} = 2$ V	0	0.3		0	0.3		V
	$V_{CC} = 4.5$ V	0	0.9		0	0.9		
	$V_{CC} = 6$ V	0	1.2		0	1.2		
V_I Input voltage		0	V_{CC}		0	V_{CC}		V
V_O Output voltage		0	V_{CC}		0	V_{CC}		V
T_A Operating free-air temperature		-55	125		-40	85		°C

2 HCMOS Devices

SN54HC14, SN74HC14
HEX SCHMITT-TRIGGER INVERTERS

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	V _{CC}	T _A = 25 °C			SN54HC14		SN74HC14		UNIT
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
V _{OH}	V _I = V _{IH} or V _{IL} , I _{OH} = -20 μA	2 V	1.9	1.998		1.9		1.9	V	
		4.5 V	4.4	4.499		4.4		4.4		
		6 V	5.9	5.999		5.9		5.9		
	4.5 V	3.98	4.30		3.7		3.84			
	V _I = V _{IH} or V _{IL} , I _{OH} = -5.2 mA	6 V	5.48	5.80		5.2		5.34		
V _{OL}	V _I = V _{IH} or V _{IL} , I _{OL} = 20 μA	2 V		0.002	0.1		0.1		0.1	V
		4.5 V		0.001	0.1		0.1		0.1	
		6 V		0.001	0.1		0.1		0.1	
	4.5 V		0.17	0.26		0.4		0.33		
	V _I = V _{IH} or V _{IL} , I _{OL} = 5.2 mA	6 V		0.15	0.26		0.4		0.33	
V _{T+}		2 V	0.70	1.2	1.50	0.70	1.50	0.70	1.50	V
		4.5 V	1.55	2.5	3.15	1.55	3.15	1.55	3.15	
		6 V	2.10	3.3	4.20	2.10	4.20	2.10	4.20	
V _{T-}		2 V	0.30	0.6	1.00	0.30	1.00	0.30	1.00	V
		4.5 V	0.90	1.6	2.45	0.90	2.45	0.90	2.45	
		6 V	1.20	2.0	3.20	1.20	3.20	1.20	3.20	
V _{T+} - V _{T-}		2 V	0.20	0.6	1.20	0.20	1.20	0.20	1.20	V
		4.5 V	0.40	0.9	2.10	0.40	2.10	0.40	2.10	
		6 V	0.50	1.3	2.50	0.50	2.50	0.50	2.50	
I _I	V _I = V _{CC} or 0	6 V	±0.1 ±100			±1000		±1000		nA
I _{CC}	V _I = V _{CC} or 0, I _O = 0	6 V	2			40		20		μA
C _i		2 to 6 V	3 10			10		10		pF

2
HCMOS Devices

switching characteristics over recommended operating free-air temperature range (unless otherwise noted), C_L = 50 pF (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC}	T _A = 25 °C			SN54HC14		SN74HC14		UNIT
				MIN	TYP	MAX	MIN	MAX	MIN	MAX	
t _{pd}	A	Y	2 V		55	125		190		155	ns
			4.5 V		12	25		38		31	
			6 V		11	21		32		26	
t _t		Y	2 V		38	75		110		95	ns
			4.5 V		8	15		22		19	
			6 V		6	13		19		16	

C _{pd}	Power dissipation capacitance per inverter	No load, T _A = 25 °C	20 pF typ
-----------------	--	---------------------------------	-----------

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.



POST OFFICE BOX 655012 • DALLAS, TEXAS 75265