

P.C. JACKS-CLOSED ENTRY-SOLDER MOUNT

09-9008-1-XX P.C. JACK FOR .040 PIN

BASIC PART NO. FINISH

ACCEPTS .040 PIN BOARD THICKNESS .031 TO .094
RECOMMENDED MOUNTING HOLE .089±.002(#43 DRILL)

09-9159-1-XX P.C. JACK FOR .060, .061 AND .062 PINS*

BASIC PART NO. FINISH

ACCEPTS .060, .061 AND .062 PIN*
RECOMMENDED MOUNTING HOLE 102±.001(#38 DRILL)
*USE ONE SIZE PIN ONLY-NOT RECOMMENDED FOR SMALLER PIN USE AFTER LARGER PIN HAS BEEN USED

09-9006-1-XX .040 JACK-SPECIAL PRESS FIT RETENTION FEATURE

BASIC PART NO. FINISH

ACCEPTS .040 PIN BOARD THICKNESS .062 TO .125
RECOMMENDED MOUNTING HOLE .076±.001(#48 DRILL)

09-9039-1-XX P.C. JACK FOR .080 PIN

BASIC PART NO. FINISH

ACCEPTS .080 PIN BOARD THICKNESS .031 TO .250
RECOMMENDED MOUNTING HOLE .144±.001(#27 DRILL)

09-9061-1-XX P.C. JACK FOR .050 PIN

BASIC PART NO. FINISH

ACCEPTS .050 PIN BOARD THICKNESS .031 TO .156
RECOMMENDED MOUNTING HOLE .102±.002(#38 DRILL)

09-9044-1-XX P.C. JACK FOR .080 PIN

BASIC PART NO. FINISH

ACCEPTS .080 PIN BOARD THICKNESS .031 TO .250
RECOMMENDED MOUNTING HOLE .144±.001(#27 DRILL)

09-9013-1-XX P.C. JACK FOR .060, .061 AND .062 PIN*

BASIC PART NO. FINISH

ACCEPTS .060, .061 AND .062 PIN* BOARD THICKNESS .031 TO .156
RECOMMENDED MOUNTING HOLE .102±.002(#38 DRILL)
*USE ONE SIZE PIN ONLY-NOT RECOMMENDED FOR SMALLER PIN USE AFTER LARGER PIN HAS BEEN USED

09-9038-1-XX P.C. JACK FOR .080 PIN-SOLDER MOUNT

BASIC PART NO. FINISH

ACCEPTS .080 PIN BOARD THICKNESS .031 TO .312
RECOMMENDED MOUNTING HOLE .116±.002(#32 DRILL)

MATERIAL Body: Brass per ASTM B16 Spring Contact: Beryllium Copper per ASTM B194

FINISH	Part Number/Finish Code	Body Finish	Spring Contact Finish
	09-9XXX-X-03	Gold per ASTM B488	Gold per ASTM B488
	04	Electro-Tin per ASTM B545	Electro-Tin per ASTM B545
	06	Electro-Tin per ASTM B545	Gold per ASTM B488
	063	Bright Tin-Lead per ASTM B545	Gold per ASTM B488
	088	Bright Tin-Lead per ASTM B545	Bright Tin-Lead per ASTM B545

FOR ADDITIONAL SIZES AND MATERIALS, CONTACT FACTORY

e-mail : info@concord-elex.com
800-847-4162 (outside N.Y.S.)
212-777-6571 • fax. 212-995-0161



11/83/THX