

V _{CE(sust)} (Volts) Min	Devices		I _C Max (Amps)	h _{FE} @ I _C			V _{CE(sat)} @ I _C & I _B			f _T (MHz) Min	Package	P _D (Amb) (Watts) @25°C	
	NPN	PNP		Min	Max	mA	(Volts) Max	mA	μA				
40	2N6724		1	25,000		200	1.0	200	2mA	100	TO-237(91)	0.85	
				15,000		500	1.5	1A					
				4,000	40,000	1A							
		D40C4		1	10,000	60,000	200	1.5	500	500		TO-202(55)	1.3
		D40C5		1	40,000		200	1.5	500	500		TO-202(55)	1.3
		NSD154		1	20,000		10	1.5	100	100		TO-202(55)	1.3
					5,000		100						
		NSDU45		1	25,000	150,000	200	1.0	200	2mA	100	TO-202(55)	1.3
15,000						500	1.5	1A	2mA				
4,000						1A							
30	BC517	BC516	1	30,000		20	1.0	100	100		TO-92(97)	0.6	
	BCV27	BCV26	1	4,000		1	1.0	100	100		TO-236*	0.35	
				10,000		10							
				20,000		100							
		D40C1		1	10,000	60,000	200	1.5	500	500		TO-202(55)	1.3
		D40K1		1	10,000		200	1.5	1.5A	3mA		TO-202(55)	1.3
					1,000		1.5A						
		MMBTA13		1	5,000		10	1.5	100	100	125	TO-236*	0.35
					10,000		100						
		MMBTA14		1	10,000		10	1.5	100	100	125	TO-236*	0.35
					20,000		100						
		MPSA13	MPSA63	1	5,000		10	1.5	100	100	125	TO-92(92)	0.625
10,000						100							

* TO-236AB is standard for all devices.
Please refer to Surface Mount section for TO-236 Device Marking.

6

NATL SEMICOND (DISCRETE)

