

Intel® Xeon® Processor E3-1270 v5 (8M Cache, 3.60 GHz)

Compare +

Related Products

- Intel® Xeon® Processor E3 v5 Family
- Intel® Xeon® Processor E3-1200 v5 Product Family
- Products formerly Skylake



Learn how Intel is pursuing conflict-free technology. >

Quick Links

- Export Full Specifications >
- Support Overview >
- Search Distributors >

PCN/MDDS Information

SR2LF
947229: PCN | MDDS
947518: PCN | MDDS

Specifications

- Essentials
- Performance
- Memory Specifications
- Graphics Specifications
- Expansion Options
- Package Specifications
- Advanced Technologies
- Intel® Data Protection Technology
- Intel® Platform Protection Technology

Compatible Products

Ordering / sSpecs / Steppings

Download Drivers

Specifications

Essentials

Status	Launched
Launch Date	Q4'15
Processor Number	E3-1270V5
Cache	8 MB SmartCache
Bus Speed	8 GT/s DMI3
Instruction Set	64-bit
Instruction Set Extensions	SSE4.1/4.2, AVX 2.0
Embedded Options Available	No
Lithography	14 nm
Scalability	1S Only
VID Voltage Range	0.55V-1.52V
Recommended Customer Price	\$328.00 - \$339.00
Conflict Free	Yes
Datasheet	Link

Performance

# of Cores	4
# of Threads	8
Processor Base Frequency	3.6 GHz
Max Turbo Frequency	4 GHz
TDP	80 W

Memory Specifications

Max Memory Size (dependent on memory type)	64 GB
Memory Types	DDR4-1866/2133, DDR3L-1333/1600 @ 1.35V
Max # of Memory Channels	2
Max Memory Bandwidth	34.1 GB/s
ECC Memory Supported †	Yes

Graphics Specifications

Processor Graphics †	None
Graphics Output	N/A
4K Support	No
Max Resolution (Intel® WiDi) ‡	N/A
Max Resolution (HDMI 1.4) ‡	N/A
Max Resolution (DP) ‡	N/A
Max Resolution (eDP - Integrated Flat Panel) ‡	N/A
Max Resolution (VGA) ‡	N/A
DirectX® Support	N/A
OpenGL® Support	N/A
Intel® Quick Sync Video	No
Intel® InTru™ 3D Technology	No
Intel® Insider™	No
Intel® Wireless Display	No
Intel® Clear Video HD Technology	No
Intel® Clear Video Technology	No
# of Displays Supported †	0

Expansion Options

PCI Express Revision	3.0
PCI Express Configurations †	1x16, 2x8, 1x8+2x4
Max # of PCI Express Lanes	16

Package Specifications

Max CPU Configuration	1
Package Size	37.5mm x 37.5mm
Graphics and IMC Lithography	14 nm
Sockets Supported	FCLGA1151
Low Halogen Options Available	See MDDS

Advanced Technologies

Intel® Turbo Boost Technology †	2.0
Intel® vPro Technology †	Yes
Intel® Hyper-Threading Technology †	Yes
Intel® Virtualization Technology (VT-x) †	Yes
Intel® Virtualization Technology for Directed I/O (VT-d) †	Yes
Intel® VT-x with Extended Page Tables (EPT) †	Yes
Intel® TSX-NI	Yes
Intel® 64 †	Yes
Idle States	Yes
Enhanced Intel SpeedStep® Technology	Yes
Thermal Monitoring Technologies	Yes

Intel® Data Protection Technology

Intel® AES New Instructions	Yes
Secure Key	Yes
Intel® Software Guard Extensions (Intel® SGX)	Yes
Intel® Memory Protection Extensions (Intel® MPX)	Yes

Intel® Platform Protection Technology

OS Guard	Yes
Trusted Execution Technology †	Yes
Execute Disable Bit †	Yes

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

"Intel classifications" consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company may be the exporter of record, and as such, your company is responsible for determining the correct classification of any item at the time of export.

Refer to Datasheet for formal definitions of product properties and features.

*Announced SKUs are not yet available. Please refer to the Launch Date for market availability.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

‡ This feature may not be available on all computing systems. Please check with the system vendor to determine if your system delivers this feature, or reference the system specifications (motherboard, processor, chipset, power supply, HDD, graphics controller, memory, BIOS, drivers, virtual machine monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

"Conflict free" and "conflict-free" means "DRC conflict free", which is defined by the U.S. Securities and Exchange Commission rules to mean products that do not contain conflict minerals (tin, tantalum, tungsten and/or gold) that directly or indirectly finance or benefit armed groups in the Democratic Republic of the Congo (DRC) or adjoining countries. Intel also uses the term "conflict-free" in a broader sense to refer to suppliers, supply chains, smelters and refiners whose sources of conflict minerals do not finance conflict in the DRC or adjoining countries. Intel processors manufactured before January 1, 2013 are not confirmed conflict free. The conflict free designation refers only to product manufactured after that date. For Intel Boxed Processors, the conflict free designation refers to the processor only, not to any additional included accessories, such as heatsinks/coolers.

See <http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html?wapkw=hyper-threading> for more information including details on which processors support Intel® HT Technology.

Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See www.intel.com/technology/turboboost/ for more information.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers, typically represent 1,000-unit purchase quantities, and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply. If sold in bulk, price represents individual unit. Listing of these RCP does not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components in the finished assembly meet J5-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

For benchmarking data see <http://www.intel.com/performance>.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See <http://www.intel.com/content/www/us/en/processors/processor-numbers.html> for details.

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.

Send us your feedback!

USA (English)

Company Information Our Commitment Communities Investor Relations Contact Us

Newsroom Jobs



© Intel Corporation | Terms of Use | Trademarks | Privacy | Cookies | Supply Chain Transparency | Site Map

www.datasheetlive