

Search within category **GO**

**BUY NOW**

**DESIGN / INSTALL**



**PK6-14R-T**

Ring terminal, #6 AWG, KYNAR insulated, 1/4" stud size.

**Specs** Packaging Details Tools Documents [★ Add to Favorites](#) [Add to BOM](#)

Stud Size	1/4"
Wire Range	6 AWG
Wire Range (mm <sup>2</sup> )	16
Barrel Configuration	Standard
Barrel Type	Insulation Grip Sleeve
Base Material	Copper
Insulation	Kynar
Panduit Color Code	Blue Stripe
Plating Type	Tinned
Part Number Series	PK
Clearance	0.48
Clearance (mm)	12.2
Length (In.)	1.63
Length (mm)	41.4
Max. Insulation Diameter In. (mm)	0.360 (9.14)
Stock	0.05
Stock (mm)	1.1
Width (In.)	0.47
Width (mm)	11.9
Wire Strip Length (In.)	7/16" (.4375)
Wire Strip Length (mm)	11.11
Flammability Rating	UL 94V-0
Max. Voltage Rating	600 V
Temperature Rating	300 Degrees Fahrenheit (150 Degrees Celsius)
CA-800/EZ Series Crimp Die	—
CA9 Series Crimp Die	—
Tool	CT-2600, CD-2600-PV6
CSA Certified	C22.2 No. 65
Mil. Std. Part Number	—
Standards	IEEE 323-2003
UL Listed	UL 486A - UL 486B
Packaging Type	Box

www.datasheetline.com

Part Features

- For nuclear containment areas and high temperature to 300°F (150°C) applications
- Color code: natural with appropriate color stripe to identify wire range
- Ring tongue design assures a secure connection in high vibration applications

Stud Size Metric

M6

RoHS Compliancy Status

Compliant

Min. Order Qty.

200