

Resonators > CERALOCK (MHz) > Part Number








How to check EU RoHS Compliance of Our Products is [here](#).

Product Lifecycle Stage	in Production
Recommended Rank	Preferred

Specifications

Global Part Number	CSTLS10M0G53-B0
Previous Part Number	
Nominal Frequency	10.000MHz
Initial Tolerance	±0.5%
Resonant Frequency	25ohm
Temp. Stability	±0.2%
Operating Temperature Range	-20 to +80°C
Frequency Aging	±0.2%
Wash	Not Available
Ultrasonic Wash	Not Available
Built-in Load Capacitance	15pF
Use	For consumer electronics

Details

-  [Part Numbering](#)
-  [Appearance](#)
-  [Dimensions](#)
-  [Features_and_Applications](#)
-  [Temperature_Characteristics](#)
-  [Basic_Oscillation_Circuit](#)
-  [Notice](#)

Minimum Quantity

180mm Paper Tape	
180mm Embossed Tape	
330mm Paper Tape	
330mm Embossed Tape	
Bulk Case	
Bulk(Bag)	500
Ammo Pack	
320Reel	
Magazine	
Box	

Please approve our product specifications or to transact the approval sheet for product specifications before ordering.

Please read **rating** and **!Cautions** first.

Product specifications in this catalog are as of May 2013

Please make sure to read the Murata's [Product Policy](#), too.

All products and company names herein are trademarks or registered trademarks of their respective owners.