

| | | | | | |
|--------------------|--------|--|------------|-------------|-----------|
| MC 1416 L,P | LIN-IC | =ULN 2004A | 16-DIC/DIP | - | |
| MC 1455 G | LIN-IC | =MC 1455P1: Fig. → | TO-99 | - | |
| MC 1455 P1 | LIN-IC | Zeitgeber/timer, 18V, 0...+70° | 8-DIP | NE 555 N | 8-DIP |
| MC 1455 U | LIN-IC | =MC 1455P1: Fig. → | 8-DIP | (NE 555 N) | 8-DIP |
| MC1458(C,N)G,H,L,T | OP-IC | Dual, Serie 158, ±18V, 0...+70°, 0,5V/µs | TO-99 | 4558/8-D | 8-DIP |
| MC 1458 JG,P | OP-IC | =MC 1458(C,N)G,H: Fig. → | 8-DIP/DIC | 4558/8-D | 8-DIP |
| MC 1458(C,N)P1,U | OP-IC | =MC 1458(C,N)G,H: Fig. → | 8-DIP/DIC | 4558/8-D | 8-DIP |
| MC 1458 S | OP-IC | =MC 1458(C,N)G,H: Fig. → | 9-SIP | - | |
| MC 1555 G | LIN-IC | =MC 1455P1: -55...+125° | TO-99 | - | |
| MC 1555 U | LIN-IC | =MC 1455P1: -55...+125° | 8-DIC | - | |
| MC 1558(N)JG,N,U,P | OP-IC | =MC 1458(C,N)G,H: ±22V, -55...+125° | 8-DIC/DIP | - | |
| MC 1723 CG | Z-IC | =MC 1723G: 0...+70° | TO-100 | 723/TO | TO-100 |
| MC 1723 CL,CP | Z-IC | =MC 1723CG: 0...+70° | 14-DIC/DIP | 723/14-D | 14-DIP |
| MC 1741(N)CG | OP-IC | =MC 1741(N)G: ±18V, 0...+70° | TO-99 | 741/TO | TO-99 * |
| MC 1741(N)CL,CP2 | OP-IC | =MC 1741(N)G: ±18V, 0...+70° | 14-DIC/DIP | - | |
| MC 1741(N)CP1 | OP-IC | =MC 1741(N)G: Fig. → | 8-DIP | - | |
| MC 1741(N)CU | OP-IC | =MC 1741(N)G: ±18V, 0...+70° | 8-DIC | (741/8-D) | 8-DIP |
| MC 1741(N)G | OP-IC | Serie 741, ±22V, -55...+125°, 0,5V/µs | TO-99 | - | |
| MC 1741(N)L,P2 | OP-IC | =MC 1741(N)G: Fig. → | 14-DIC/DIP | - | |
| MC 1741 SCG | OP-IC | =MC 1741(N)G: ±18V, 0...+70°, >10µs | TO-99 | - | |
| MC 1741 SCP1 | OP-IC | =MC 1741(N)G: ±18V, 0...+70°, >10µs | 8-DIP | - | |
| MC 1741 SG | OP-IC | =MC 1741(N)G: >10µs | TO-99 | - | |
| MC 1741(N)U | OP-IC | =MC 1741(N)G: Fig. → | 8-DIC | - | |
| MC 1747 CG | OP-IC | =MC 1747G: ±18V, 0...+75° | TO-100 | - | |
| MC 1747 CL,CP2 | OP-IC | =MC 1747G: ±18V, 0...+75° | 14-DIC/DIP | 747/14-D | 14-DIP |
| MC 1747 G | OP-IC | Dual, Serie 747, ±22V, -55...+125° | TO-100 | - | |
| MC 1747 L | OP-IC | =MC 1747G: Fig. → | 8-DIC | - | |
| MC 1748 CG | OP-IC | =MC 1748G: ±18V, 0...+70° | TO-99 | 748/TO | TO-99 * |
| MC 1748 CP1,CU | OP-IC | =MC 1748G: ±18V, 0...+70° | 8-DIP/DIC | 748/8-D | 8-DIP |
| MC 1748 G | OP-IC | Serie 748, ±22V, -55...+125° | TO-99 | - | |
| MC 1748 U | OP-IC | =MC 1748G: Fig. → | 8-DIC | - | |
| MC 3301 L,P | OP-IC | Quad, +28/0V, 50mA, -40...+85° | 14-DIC/DIP | - | |
| MC 3302 D | KOP-IC | =MC 3302N,P: SMD | 14-MDIP | - | |
| MC 3302 F,J,L | KOP-IC | =MC 3302N,P: Fig. → | 14-DIC | (LM 339 N) | 14-DIP 16 |
| MC 3302 N,P | KOP-IC | Quad, Serie 139, +28/0V, -40...+85° | 14-DIP | (LM 339 N) | 14-DIP 16 |
| MC 3303 D | OP-IC | =MC 3303N,P: SMD | 14-MDIP | - | |
| MC 3303 F,J,L | OP-IC | =MC 3303N,P: Fig. → | 14-DIC | (LM 324 N) | 14-DIP 16 |
| MC 3303 N,P | OP-IC | Quad, Serie 124, ±18V, -40...+85° | 14-DIP | (LM 324 N) | 14-DIP 16 |
| MC 3358 P1 | OP-IC | Dual, Serie 158, lo-power, -40...+85°C | 8-DIP | (4558/8-D) | 8-DIP |
| MC 3401 P | OP-IC | =MC 3301L,P: 0...+70° | 14-DIP | - | |
| MC 3403 D,FP | OP-IC | =MC 3303N,P: SMD, 0...+70° | 14-MDIP | - | |
| MC 3403 DP,N,P | OP-IC | =MC 3303N,P: 0...+70° | 14-DIP | LM 324 N | 14-DIP |
| MC 3403 F,J,L | OP-IC | =MC 3303N,P: 0...+70° | 14-DIC | LM 324 N | 14-DIP |
| MC 3456 L,P | LIN-IC | 2x Zeitgeber/timer, 18V, 0...+70° | 14-DIC/DIP | NE 556 N | 14-DIP * |
| MC 3458 G | OP-IC | =MC 3358P1: 0...+70°C | TO-99 | - | |
| MC 3458 P1 | OP-IC | =MC 3358P1: 0...+70°C | 8-DIP | 4558/8-D | 8-DIP |
| MC 3458 U | OP-IC | =MC 3358P1: 0...+70°C | 8-DIC | (4558/8-D) | 8-DIP |
| MC 3503 DG,F,J,L | OP-IC | =MC 3303N,P: -55...+125° | 14-DIC | - | |
| MC 3556 L | LIN-IC | =MC 3456: -55...+125° | 14-DIC | - | |
| MC 3558 G | OP-IC | =MC 3358P1: -55...+125°C | TO-99 | - | |
| MC 3558 U | OP-IC | =MC 3358P1: -55...+125°C | 8-DIC | (4558/8-D) | 8-DIP |
| MC 4558 S | OP-IC | =MC 4558CH: Fig. → | 9-SIP | - | |
| MC 4558(A)CD,CFP | OP-IC | =MC 4558CH: SMD | 8-MDIP | 4558/8(SMD) | 8-MDIP |
| MC 4558(A,N)CDP,CP | OP-IC | =MC 4558CH: Fig. → | 8-DIP | 4558/8-D | 8-DIP |
| MC 4558(N)CH,CG | OP-IC | Dual, Serie 158, ±18V, 0...+70° | TO-99 | - | |
| MC 4558 G,NG,MH | OP-IC | =MC 4558CH: -55...+125° | TO-99 | - | |