



Electrical Commercial and Industrial

- Products
- Documentation & Literature
- News & Tradeshows
- Support

United States > Products & Services > Electronics, Electrical, and Communications > Electrical Commercial and Industrial > Products > Electrical Commercial & Industrial Products Catalog > Electrical Tape, Mastics & Special Use > Rubber Tapes - Insulating and Splicing > Scotch® Linerless Rubber Splicing Tape 130C-3/4x30FT, 3/4 in x 30 ft (19 mm x 9,1 m), 24 per case

Find An Account Rep Where To Buy (Find A Distributor) Contact Us

Scotch® Linerless Rubber Splicing Tape 130C-3/4x30FT, 3/4 in x 30 ft (19 mm x 9,1 m), 24 per case

UPC# 00054007417170 3M Product Number 130C-3/4X30FT 3M ID 80610833404 Print Share



This is a highly conformable, linerless Ethylene Propylene Rubber (EPR), high-voltage insulating tape that provides excellent thermal dissipation of splice heat. Packed 1 per box with 24 rolls per case.

Network Access Message: The page

Buy Online at Shop3M.com

Need Help?

Questions? We can help

Contact Us

- Overview
- Support

Specifications

Adhesive Material	Rubber Resin
Agency Approvals	ASTM D-4388 type 1, 2 & 3 HH-I-3825B
Backing Material	Ethylene Propylene Rubber
China RoHS - Below MCV	Yes
Color	Black
Dielectric Strength (V/mil)	750 V/mil
Emergency Overload Temperature Range	130 Degree Celsius
EU RoHS Compliant	Yes
Length	30 Linear Foot
Maximum Operating Temperature (Celsius)	90 Degree Celsius
Operating Temperature Range	-18 to 90 Degree Celsius
Operating Temperature Range (Fahrenheit)	0 to 194 Degree Fahrenheit
Product Family	Scotch® Linerless Rubber Splicing Tape 130C
Tape Color	Black
Tape Grade	Premium
Tape Length	30 Linear Foot
Tape Type	Rubber Insulating and Splicing
Tape Width	0.75 in
Tensile Strength	250 Pound-Force Per Square Inch
Tensile Strength lb/in (N/100 mm)	7.5 (131)
Thickness	30 Milli-inch (mil)
Width	0.75 Inch

