

— Numerical Index —

2N342-2N414

TYPE	MATERIAL	POLARITY	REPLACE- MENT	PAGE NUMBER	USE	MAXIMUM RATINGS					ELECTRICAL CHARACTERISTICS							
						P _D @ 25°C	T _J Ref Point	V _{CB} °C	V _{CE} — (volts)	I _C (volts)	h _{FE} @ I _C (min) (max)	V _{CE(SAT)} @ I _C (volts)	f _T (min) (max)	h _{FE} — Units	f _T Subscript	f _T Units	f _T Subscript	
2N342	S	N			AFA	1.0W	C	150	60	60	0				0.9	B		
2N342A	S	N			AFA	1.0W	C	150	85	85	0				0.9	B		
2N342B	S	N			AFA	750M	A	175	85	85	0				9.0	E		
2N343	S	N			AFA	1.0W	C	150	60	60	0				0.966	B		
2N343A	S	N			AFA	1.0W	C	150	60	60	0				0.966	B		
2N343B	S	N			AFA	750M	A	175	65	65	0				28	E		
2N344	G	P			RFC	20M	A	55	5.0	5.0	0				11	E	30M	M
2N345	G	P			RFC	20M	A	55	5.0	5.0	0				25	E	30M	M
2N346	G	P			RFC	20M	A	55	5.0	5.0	0				10	E	60M	M
2N350	G	P		7-30	LPA	10W	A	100	50	40	0	20	60	700M				
2N350A	G	P		7-30	LPA	90W	J	100	50	40	0	20	60	0.7A				
2N351	G	P		7-30	LPA	10W	A	100	50	40	0	25	90	700M	1.75	3.0A		5.0K
2N351A	G	P		7-30	LPA	90W	J	100	50	40	0	25	90	0.7A				5.0K
2N352	G	P	2N1536	7-60	LPA	25W	C	100	40	40	0	30	140	1.0A				10K
2N353	G	P	2N1536	7-60	LPA	30W	C	100	40	40	0	40	150	1.0A				7.0K
2N354	S	N			RFA	150M	A	140	25	25	0				9.0	E	8.0M	M
2N355	S	N			MSS	150M	A	140	10	10	0				9.0	E	8.0M	M
2N356	S	N			MSA	100M	A	85	20	18	0	20	50	100M	0.15	5.0M		
2N356A	S	N			MSA	150M	A	100	30	20	0	20	50	100M	0.2	100M		
2N357	G	N			MSA	100M	A	85	20	15	0	20	50	200M	0.2	200M		
2N357A	G	N			MSA	150M	A	100	30	20	0	25	75	200M	0.2	200M		
2N358	G	N			MSA	100M	A	85	20	12	0	20	50	300M	0.2	300M		
2N358A	G	N			MSA	150M	A	100	30	15	0	25	75	300M	0.2	300M		
2N359	G	P	2N652	6-20	AFC	170M	A	85	25	18	0	100	300	50M				
2N360	G	P	2N1192	6-30	AFC	170M	A	85	32	30	0	50	150	50M				
2N361	G	P	2N1191	6-30	AFC	170M	A	85	32	30	0	25	75	50M				
2N362	G	P	2N1192	6-30	AFC	170M	A	85	25	18	0							
2N363	G	P	2N1191	6-30	AFC	170M	A	85	32	28	0							
2N364	G	N			MSA	150M	A	100	30	30	0				50	E	1.0M	B
2N365	G	N			MSA	150M	A	100	30	30	0				25	E	1.0M	B
2N366	G	N			MSA	150M	A	100	30	30	0				19	E	1.0M	B
2N367	G	P	2N1191	6-30	MSA	100M	A	75	30	30	0				9.0	E	300K	B
2N368	G	P	2N1191	6-30	MSA	100M	A	75	30	30	0				19	E	400K	B
2N369	G	P	2N1191	6-30	MSA	100M	A	75	30	30	0				49	E	500K	B
2N370	G	P	2N3324	9-71	RFC	80M	A	71	24	24	0							
2N371	G	P	2N3324	9-71	RFC	80M	A	71	24	24	0							
2N372	G	P	2N3324	9-71	RFC	80M	A	71	24	24	0							
2N373	G	P			RFC	80M	A	71	25	25	0							
2N374	G	P	2N3325	9-71	RFC	80M	A	71	25	25	0							
2N375	G	P		7-32	LPA	58W	C	95	80	80	0	35	90	1.0A				
2N376	G	P		7-30	LPA	10W	A	100	50	40	0	35	120	700M	1.0	2.0A		7.0K
2N376A	G	P		7-30	LPA	90W	J	100	50	40	0	35	120	0.7A	1.75	5.0A		5.0K
2N377	G	N			MSS	150M	A	100	25	20	0	20	60	30M	0.5	200M		5.0M
2N377A	G	N			MSS	150M	A	100	40	40	0	20	60	30M				
2N378	G	P		7-35	PMS	50W	C	100	20	20	0	40	80	2.0A	1.0	2.0A		5.0K
2N379	G	P		7-35	PMS	50W	C	100	40	40	0	20	70	2.0A	1.0	2.0A		5.0K
2N380	G	P		7-35	PMS	50W	C	100	30	30	0	30	70	2.0A	1.0	2.0A		5.0K
2N381	G	P		6-10	AFA	0.2W	A	100	50	25	0	35	65	20M				5.0K
2N382	G	P		6-10	AFA	0.2W	A	100	50	25	0	60	95	20M				
2N383	G	P		6-10	AFA	0.2W	A	100	50	25	0	75	120	20M				
2N384	G	P	2N3325	9-71	RFC	120M	A	100	40	40	0	20	175	1.5M				
2N385	G	N			MSS	150M	A	100	25	25	0	30	110	30M				4.0M
2N385A	G	N			MSS	150M	A	100	40	40	0	30	110	30M				4.0M
2N386	G	P	2N1531	7-60	LPA	500M	C	100	60	60	0	20	2.5A					7.0K
2N387	G	P	2N1531	7-60	LPA	500M	C	100	80	80	0	20	2.5A					6.0K
2N388	G	N			MSS	150M	A	100	25	20	0	60	180	30M				5.0M
2N388A	G	N			MSS	150M	A	100	40	40	0	60	200	0.30M				5.0M
2N389	S	N	2N3445	7-111	LPA	85W	C	200	60	60	0	12	60	1.0A				
2N389A	S	N			LPA	85W	C	200	60	60	0	12	60	1.0A	0.75	1.0A		1.0M
2N392	G	P	2N1550	7-67	LPA	48W	C	95	60	40	0	60	150	3.0A	0.5	3.0A		
2N393	G	P	2N967	8-76	MSS	25M	A	100	6.0	6.0	0	20	50M	0.07	8.0M		40	25M
2N394	G	P			HSA	150M	A	85	10	10	0	20	150	10M				4.0M
2N394A	G	P			HSA	150M	A	85	10	10	0	30	120	10M				4.0M
2N395	G	P			HSA	200M	A	100	30	15	0	20	150	10M	0.2	50M		3.0M
2N396	G	P			HSA	200M	A	100	30	20	0	30	150	10M	0.2	50M		5.0M
2N396A	G	P			HSA	200M	A	100	30	20	0	30	150	10M	0.2	50M		5.0M
2N397	G	P			HSA	200M	A	100	30	15	0	40	150	10M	0.2	50M		10M
2N398	G	P		6-12	IND	50M	A	55	105	105	0	20	5.0M					
2N398A	G	P		6-12	AFA	150M	A	100	105	105	0	20	5.0M	0.35	5.0M		20	1.0M
2N398B	G	P	2N2043	6-39	IND	250M	A	100	105	105	0	20	5.0M	0.25	5.0M		40	1.0M
2N399	G	P	2N351A	7-30	LPA	25W	C	90	35	35	0			1.0	1.2A			
2N400	G	P	2N350A	7-30	LPA	35W	C	95	25	20	0	40	300	0.5A	0.8	1.0A	25	3.0K
2N401	G	P	2N3611	7-118	LPA	25W	C	90	35	35	0			1.0	1.2A			
2N402	G	P	2N1191	6-30	AFA	180M	A	85	25	20	0							
2N403	G	P	2N1191	6-30	AFA	180M	A	85	25	20	0							
2N404	G	P			MSS	150M	A	85	25	25	0							
2N404A	G	P			MSS	150M	A	100	40	40	0	30		12M	0.15	12M		4.0M
2N405	G	P	2N322	6-7	AFC	150M	A	71	20	20	0							
2N406	G	P	2N322	6-7	AFC	150M	A	71	20	20	0							
2N407	G	P	2N324	6-7	AFC	150M	A	71	20	20	0							
2N408	G	P	2N324	6-7	AFC													

COMPLETE NUMERICAL-ALPHABETICAL LISTING

Type	MAXIMUM RATINGS					ELECTRICAL CHARACTERISTICS					MILITARY and Hi-Rel Type
	P _D mW	T _J °C	V _{CSO} volts	V _{CEB} (R = 10 k) volts	I _C mA	h _{FE} @ V _{CE} & I _C				f _{αB} typ MHz	
						min	max	volts	mA		
2N319	225	100	—	20	500	25	42	1	20	1.0 ⑤	
2N320	225	100	—	20	500	34	65	1	20	1.5 ⑤	
2N321	225	100	—	20	500	53	121	1	20	2.0 ⑤	
2N322	225	100	—	18	500	34	65	1	20	1.0 ⑤	
2N323	225	100	—	18	500	53	121	1	20	1.5 ⑤	
2N324	225	100	—	18	500	72	198	1	20	2.0 ⑤	
2N331	200	100	30	V _{EB} = 12	200	30	70	6	1	1.5	JAN 2N331
2N381	225	100	50	25	400	35	65	1	20	3	
2N382	225	100	50	25	400	60	95	1	20	4	
2N383	225	100	50	25	400	75	120	1	20	5	
2N398	50	85	105	V _{pt} = 105	100	20	—	0.35	5	1.0	USN 2N398
2N398A	150	100	105	V _{pt} = 105	200	20	—	0.35	5	1.0	
2N460	225	100	45	35 ⑦	400	31	200	6	1 ②	4	
2N461	225	100	45	35 ⑦	400	0.94 h _b	0.972	6	1 ②	1.2	USAF 2N461
2N464	200	100	45	40	100	14	—	6	1	1.0	
2N465	200	100	45	30	100	27	—	6	1	1.5	USA 2N465
2N466	200	100	35	20	100	56	—	6	1	2.0	JAN 2N466
2N467	200	100	35	15	100	112	—	6	1	2.5	USA 2N467
2N508	225	100	—	18	500	99	198	1	20	2.5 ⑤	
2N524	225	100	—	30	500	25	42	1	20	0.8 ⑤	2N524A ①
2N525	225	100	—	30	500	34	65	1	20	1.0 ⑤	2N525A ①
2N526	225	100	—	30	500	53	90	1	20	1.3 ⑤	JAN 2N526
2N527	225	100	—	30	500	72	121	1	20	1.5 ⑤	2N526A ①
2N650	200	100	45	30	500	30	70	6	1	1.5	2N527A ①
											2N650A ①
2N651	200	100	45	30	500	50	120	6	1	2.0	USN 2N650A
											2N651A ①
2N652	200	100	45	30	500	100	225	6	1	2.5	USN 2N651A
											2N652A ①
											USN 2N652A
2N653	200	100	30	25	250	30	70	6	1	1.5	
2N654	200	100	30	25	250	50	125	6	1	2.0	
2N655	200	100	30	25	250	100	250	6	1	2.5	
2N1008	200	100	20	20 ⑥	300	40 h _{FE}	150	5	10	—	
2N1008A	200	100	40	40 ⑥	300	40 h _{FE}	150	5	10	—	
2N1008B	200	100	60	60 ⑥	300	40 h _{FE}	150	5	10	—	
2N1175	225	100	—	25	500	70	140	1	20	1.5 ⑤	
2N1185	200	100	45	30	500	190	400	6	1	3.0	
2N1186	200	100	60	45	500	30	70	6	1	1.5	
2N1187	200	100	60	45	500	50	120	6	1	2.0	
2N1188	200	100	60	45	500	100	225	6	1	2.5	
2N1189	200	100	45	30	500	60	—	1	10 ②	3.5	
2N1190	200	100	45	30	500	100	—	1	10 ②	4.5	
2N1191	200	100	40	25	200	30	70	6	1	1.5	
2N1192	200	100	40	25	200	50	125	6	1	2.0	

2N381 thru **2N383**
2N2171

$V_{CB} = 50 \text{ V}$
 $h_{FE} — \text{to } 110\text{-}250 \text{ (min-max)}$
 $f_{ab} — \text{to } 7.5 \text{ MHz}$

CASE 31
(TO-5)



Base connected to case

PNP germanium transistors for small-signal audio amplifiers, Class B push-pull output stages and medium-speed switching circuits.

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector-Base Voltage	V_{CB}	50	Volts
Collector-Emitter Voltage ($R_{BE} = 10K$)	V_{CER}	25	Volts
Emitter-Base Voltage	V_{EB}	20	Volts
Collector Current	I_C	400	mA
Junction Temperature	T_J	-65 to +100	$^{\circ}C$
Collector Dissipation $T_A = 25^{\circ}C$ derate $T_C = 25^{\circ}C$ derate	P_D	225 3 500 6.7	mW mW/ $^{\circ}C$ mW mW/ $^{\circ}C$

ELECTRICAL CHARACTERISTICS ($T_c = 25^{\circ}C$ unless otherwise noted)

Characteristics	Symbol	Min	Typical	Max	Unit
Collector-Base Cutoff Current ($V_{CB} = -25 \text{ Vdc}$)	I_{CBO}	---	6	10	$\mu \text{ Adc}$
Emitter-Base cutoff Current ($V_{EB} = -20 \text{ Vdc}$)	I_{EBC}	---	5	10	$\mu \text{ Adc}$
Collector-Emitter Voltage ($I_C = 500 \mu \text{ Adc}$, $R_{BE} = 10K$)	BV_{CER}	25	---	---	Vdc
Collector-Emitter Voltage ($I_C = 50 \mu \text{ Adc}$, $V_{BE} = 1.0 \text{ Vdc}$)	BV_{CER}	---	50 45	---	Vdc
DC Current Gain ($I_C = 20 \text{ mAdc}$, $V_{CE} = -1.0 \text{ Vdc}$)	h_{FE}	35 60 75 110	---	65 95 120 250	---
($I_C = 100 \text{ mAdc}$, $V_{CE} = -1.0 \text{ Vdc}$)		30 50 65 90	---	---	---

2N381 thru 2N383

2N2171 (continued)

ELECTRICAL CHARACTERISTICS (continued)

Characteristics	Symbol	Min	Typical	Max	Unit
Small Signal Current Gain ($I_C = 10 \text{ mA}$, $V_{CE} = -5.0 \text{ V}$, $f = 1 \text{ kHz}$)	h_{fe}				---
2N381		35	60	85	
2N382		70	90	135	
2N383		90	115	155	
2N2171		120	210	310	
Voltage Feedback Ratio ($I_C = 10 \text{ mA}$, $V_{CE} = -5 \text{ V}$, $f = 1 \text{ kHz}$)	h_{re}				$\times 10^{-3}$
2N381		---	0.66	---	
2N382		---	0.69	---	
2N383		---	0.72	---	
2N2171		---	0.75	---	
Input Impedance ($I_C = 10 \text{ mA}$, $V_{CE} = -5.0 \text{ V}$, $f = 1 \text{ kHz}$)	h_{ie}				ohms
2N381		---	300	---	
2N382		---	450	---	
2N383		---	550	---	
2N2171		---	850	---	
Output Admittance ($I_C = 10 \text{ mA}$, $V_{CE} = -5.0 \text{ V}$, $f = 1 \text{ kHz}$)	h_{oe}				μmhos
2N381		---	420	---	
2N382		---	400	---	
2N383		---	380	---	
2N2171		---	500	---	
Transducer Gain ($R_g = 300 \Omega$, $R_L = 500 \Omega$) ($R_g = 450 \Omega$, $R_L = 500 \Omega$) ($R_g = 550 \Omega$, $R_L = 500 \Omega$) ($R_g = 785 \Omega$, $R_L = 500 \Omega$)	G_T				dB
2N381		---	36	---	
2N382		---	38	---	
2N383		---	39.5	---	
2N2171		---	42.5	---	
Output Capacitance ($I_C = 1 \text{ mA}$, $V_{CB} = -6\text{V}$)	C_{ob}				pF
		---	20	---	
Noise Figure ($I_C = 1 \text{ mA}$, $V_{CE} = -6\text{V}$, $R_g = 1 \text{ kc}$, $f = 1 \text{ kHz}$)	NF				dB
2N381		---	6	---	
2N382		---	5.5	---	
2N383		---	5.0	---	
2N2171		---	3.5	---	
Cutoff Frequency ($I_C = 1 \text{ mA}$, $V_{CB} = -6\text{V}$)	$f_{\alpha b}$				MHz
2N381		---	3	---	
2N382		---	4	---	
2N383		---	5	---	
2N2171		---	7.5	---	