

JEDEC No.	Type	Use	MAXIMUM RATINGS				ELECTRICAL PARAMETERS						Closest GE	Dwg. No.
			Pc mw @ 25°C	BV _{CE} BV _{CB} *	Ic ma	T _J °C	MIN. hfe-hFE* @ Ic ma	MIN. fhfb mc	MIN. Ge db	MAX. Ico (µa) @ V _{CB}				
2N104	PNP		150	-30	-50	85	44		.7	33T	-10	-12	2N1415, 2N1414	24, 24
2N105	PNP		35	-25	-15	85	55	.7	.75	42	-5	-12	2N1415	24
2N106	PNP		100	-6	-10	85	25		.8	28	-12	-6	2N1097, 2N1098	24, 24
2N107	PNP	AF	50	-6	-10	60	20		.6		-10	-12	2N107, 2N1098	23, 24
2N108	PNP		50	-20	-15								2N322	3
2N109	PNP		150	-25	-70	85	75*			30T			2N1175	24
2N110	Pt		200	-50*	-50	85	32		1.5					
2N111	PNP		150	-15	200	85	15		3T	33T	-5	-12	2N394	24
2N111A	PNP		150	-15	-200	85	15		3T	33T	-5	-12	2N394	24
2N112	PNP		150	-15	-200	85	15		5T	35T	-5	-12	2N394	24
2N112A	PNP		150	-15	-200	85	15		5T	35T	-5	-12	2N394	24
2N113	PNP		100	-6	-5	85	45T		10T	33T			2N394	24
2N114	PNP		100	-6	-5	85	65T		20T				2N394	24
2N117	NPN		150	30*	25	150	.90α	1	1		10	30	2N332, 2N334	3, 3
2N118	NPN		150	30*	25	150	.95α	1	2		10	30	2N333, 2N335	3, 3
2N118A	NPN-G		150	45	25	150J	54T		7.50		10		2N335	3
2N119	NPN		150	30*	25	150	.974α	1	2		10	30	2N335, 2N336	3, 3
2N120	NPN		150	45*	25	175	.987α	1	7T		2	30		
2N122	NPN	Sw	8.75W		140A	150	3	100			10 ma	50		
2N123	PNP		150	-15	-125	85	30*	-10	5		-6	-20	2N123	23
2N124	NPN		50	10*	8	75	12*	5	3		2	5	2N293	22
2N125	NPN		50	10*	8	75	24*	5	5		2	5	2N167	22
2N126	NPN		50	10*	8	75	48*	5	5		2	5	2N167, 2N169	22, 22
2N127	NPN		50	10*	8	75	100*	5	5		2	5	2N167, 2N169	22, 22
2N128	PNP		30	-4.5	-5	85	.95	.5	45 f _{max}		-3	-5		
2N129	PNP		30	-4.5	-5	85	.92	.5	30 f _{max}		-3	-5		
2N130	PNP		85	-22	-10		22T			39T			2N1413, 2N1924	24, 24
2N130A	PNP		100	-40	-100	85	14	1	.7T	40T	-15	-20	2N1413, 2N1924	24, 24
2N131	PNP		85	-15	-10	85	45T			41T			2N1413, 2N1415	24, 24
2N131A	PNP		100	-30	-100	85	27	1	.8T	42T	-15	-20	2N1413, 2N1924	24, 24
2N132	PNP		85	-12	-10	85	90T			42T			2N1175	24
2N132A	PNP		100	-20	-100	85	56	1	1T	44T	-15	-20	2N1415	24
2N133	PNP		85	-15	-10	85	25			36T	-12	-15	2N1414	22
2N133A	PNP	Obsolete	100	-20	-100	85	50T	1	.8T	38T	-15	-20	2N1414, 2N1175	22, 24
2N135	PNP	Obsolete	100	-12	-50	85	20T		4.5T	29T			2N394	24
2N136	PNP	Obsolete	100	-12	-50	85	40T		6.5T	31T			2N394	24
2N137	PNP	Obsolete	100	-6	-50	85	60T		10T	33T			2N394	24
2N138	PNP		50	-12	-20	50	140T			30T			2N508	24
2N138A	PNP		150	-30	-100	85				29T			2N1098	24
2N138B	PNP		100	-30	-100	85				29T			2N1098	24
2N139	PNP		80	-16	-15	85	48	1	6.8	30	-6	-12	2N394	24
2N140	PNP		35	-16	-15	85	45	.4	7	27	-6	-12	2N394, 2N395	24, 24