



DEUTSCH DJT SERIES CONNECTORS FOR MIL-DTL-38999 SERIES I

RUGGED, HARSH ENVIRONMENT
SUBMINIATURE CONNECTORS

QUICK REFERENCE GUIDE

Wide Range

- Mil spec and commercial
- Range of finishes

High Performance

- Environmentally sealed

www.dataash.com



MIL-DTL-38999 Series I Connectors

| | |
|-------------------------------------|---|
| Coupling Mechanism | Bayonet, 1/3 Turn |
| Shell Materials | Aluminum |
| Features | Scoop proof Environmentally sealed Hermetic versions Filter versions Plugs with spring fingers for EMI control |
| Shell Platings | Olive drab cadmium Electroless nickel Carbon steel, electrodeposited tin plating Stainless steel, passivated |
| Contact Sizes | 22, 20, 16, 12, 10, 8 |
| Shell Sizes | 9, 11, 13, 15, 17, 19, 21, 23, 25 |
| No. of Signal Contacts, Max. | 128 |
| Contact Type | AS39029 |
| Contact Styles | Crimp Solder cup or eyelet PCB tail |
| Operating Temperatures | -65°C to +150°C - Electrodeposited tin-plated carbon steel (Class D) -65°C to +175°C - Cadmium finish (Class B) -65°C to +200°C - Nickel finish (Class F) and stainless steel (Class E) |
| Durability (Mating Cycles) | 500 |
| Standard Configurations | |
| Plugs | Straight, with EMI spring fingers (M27467) |
| Receptacles | Front, wall mount (M27466) Jam nut (M27468) Front, box mount (M27496) Rear, box mount (M27505) Rear, wall mount (M27656) Jam nut hermetic receptacle (MS27470) Solder mount hermetic receptacle (MS27471) |

TE Components . . . TE Technology . . . TE Know-how . . .
AMP | Agastat | CII | Hartman | Kilovac | Microdot | Nanonics | Polamco | Raychem | Rochester | DEUTSCH
SEACON Phoenix | L.L. Rowe | Phoenix Optix | AFP | SEACON

Get your product to market faster with a smarter, better solution.

DEUTSCH 38999 Series I Connectors



Insert Arrangements



| Insert | Contact Size/Quantity | | | | | | | | | | | QPL | QPL Hermetic | Uses 38999/62-8* Boots | Inactive: Superseded by |
|--------|-----------------------|----------|--------|---------|-----------|---------|----|----|----|----|-----|-----|--------------|------------------------|-------------------------|
| | DJT and Military | 8 Twinax | 8 Coax | 8 Power | 12 Twinax | 12 Coax | 10 | 12 | 16 | 20 | 22D | | | | |
| 09-07 | | | | | | | | | | | 7 | | | | |
| 09-35 | | | | | | | | | | | 6 | ✓ | ✓ | | |
| 09-98 | | | | | | | | | 3 | | | ✓ | ✓ | | |
| 11-02 | | | | | | | | 2 | | | | ✓ | ✓ | | |
| 11-04 | | | | | | | | | 4 | | | ✓ | ✓ | | |
| 11-05 | | | | | | | | | 5 | | | ✓ | ✓ | | |
| 11-35 | | | | | | | | | | 13 | | ✓ | ✓ | | |
| 11-98 | | | | | | | | | 6 | | | ✓ | ✓ | | |
| 11-99 | | | | | | | | | 7 | | | ✓ | ✓ | | |
| 13-04 | | | | | | | | 4 | | | | ✓ | ✓ | | |
| 13-08 | | | | | | | | | 8 | | | ✓ | ✓ | | |
| 13-35 | | | | | | | | | | 22 | | ✓ | ✓ | | |
| 13-98 | | | | | | | | | 10 | | | ✓ | ✓ | | |
| 15-05 | | | | | | | | 5 | | | | ✓ | ✓ | | |
| 15-15 | | | | | | | | 1 | 14 | | | | ✓ | | |
| 15-18 | | | | | | | | | 18 | | | | ✓ | | |
| 15-19 | | | | | | | | | 19 | | | ✓ | ✓ | | |
| 15-26 | | | | | | | | 2 | | 24 | | | | | |
| 15-35 | | | | | | | | | | 37 | | ✓ | ✓ | | |
| 15-97 | | | | | | | | 4 | 8 | | | ✓ | ✓ | | |
| 17-02 | 1 | | | | | | | | | 38 | | | | | 17-03 |
| 17-03 | 1 | | | | | | | | | 38 | | | | ✓ | |
| 17-06 | | | | | | | 6 | | | | | ✓ | | | |
| 17-08 | | | | | | | | 8 | | | | ✓ | | | |
| 17-11 | | | | 2 | 1 | | | | 8 | | | | | | |
| 17-19 | | | | | | | | 4 | 11 | 4 | | | | | |
| 17-20 | | | | | | | 4 | | | 16 | | | | | |
| 17-22 | 2 | | | | | | 2 | | | | | | | | |
| 17-24 | | | 2 | | | | | | | 22 | | | | | |
| 17-26 | | | | | | | | | 26 | | | ✓ | | | |
| 17-35 | | | | | | | | | | 55 | | ✓ | | | |
| 17-99 | | | | | | | | 2 | 21 | | | ✓ | | | |
| 19-11 | | | | | | | | 11 | | | | ✓ | | | |
| 19-18 | 4 | | | | | | | | | 14 | | | | | 19-19 |
| 19-19 | 4 | | | | | | | | | 14 | | | | ✓ | |
| 19-28 | | | | | | | | 2 | 26 | | | | | | |
| 19-32 | | | | | | | | | 32 | | | ✓ | | | |



| Insert | Contact Size/Quantity | | | | | | | | | | | QPL | QPL Hermetic | Uses 38999/62-8* Boots | Inactive: Superseded by |
|------------------|-----------------------|--------|---------|-----------|---------|----|----|----|----|-----|---|-----|--------------|------------------------|-------------------------|
| DJT and Military | 8 Twinax | 8 Coax | 8 Power | 12 Twinax | 12 Coax | 10 | 12 | 16 | 20 | 22D | | | | | |
| 19-35 | | | | | | | | | | 66 | ✓ | | | | |
| 21-11 | | | | | | | 11 | | | | ✓ | | | | |
| 21-16 | | | | | | | | 16 | | | ✓ | | | | |
| 21-20 | 2 | | | | | | | | 18 | | | | | | |
| 21-35 | | | | | | | | | | 79 | ✓ | | | | |
| 21-39 | | | | | | | | 2 | 37 | | ✓ | | | | |
| 21-41 | | | | | | | | | 41 | | ✓ | | | | |
| 21-48 | | | 4 | | | | | | | | | | | | |
| 21-75 | 4 | | | | | | | | | | | | | 21-76 | |
| 21-76 | 4 | | | | | | | | | | | | ✓ | | |
| 23-06 | 6 | | | | | | | | | | | | | | |
| 23-21 | | | | | | | | 21 | | | ✓ | | | | |
| 23-35 | | | | | | | | | | 100 | ✓ | | | | |
| 23-53 | | | | | | | | | 53 | | ✓ | | | | |
| 23-54 | | | | | | | 4 | 9 | | 40 | | | | | |
| 23-55 | | | | | | | | | 55 | | ✓ | | | | |
| 23-63 | | | | | | | 4 | 4 | | 49 | | | | | |
| 25-04 | | | | | | | | 8 | 48 | | ✓ | ✓ | | | |
| 25-07 | 2 | | | | | | | | | 97 | | | | 25-09 | |
| 25-08 | 8 | | | | | | | | | | | | | 25-10 | |
| 25-09 | 2 | | | | | | | | | 97 | | | ✓ | | |
| 25-10 | 8 | | | | | | | | | | | | ✓ | | |
| 25-17 | 6 | | | | | | | | | 36 | | | | | |
| 25-19 | | | | | | | 19 | | | | ✓ | ✓ | | | |
| 25-20 | 3 | | | | 4 | | | 13 | 10 | | | | | 25-21 | |
| 25-21 | 3 | | | | 4 | | | 13 | 10 | | | | ✓ | | |
| 25-24 | | | | | | | 12 | 12 | | | ✓ | ✓ | | | |
| 25-29 | | | | | | | | 29 | | | ✓ | ✓ | | | |
| 25-35 | | | | | | | | | | 128 | ✓ | ✓ | | | |
| 25-37 | | | | | | | | 37 | | | ✓ | ✓ | | | |
| 25-43 | | | | | | | | 20 | 23 | | ✓ | ✓ | | | |
| 25-46 | | 2 | | | | | | 4 | 40 | | | | | 25-47 | |
| 25-47 | | 2 | | | | | | 4 | 40 | | | | ✓ | | |
| 25-61 | | | | | | | | | 61 | | ✓ | ✓ | | | |
| 25-90 | 2 | | | | | | | 4 | 40 | | | | | 25-91 | |
| 25-91 | 2 | | | | | | | 4 | 40 | | | | ✓ | | |

Blue shaded entries are not Mil Spec.

LET'S CONNECT

We make it easy to connect with our experts and are ready to provide all the support you need. Just call your local support number or visit www.te.com/industrial to chat with a Product Information Specialist.

Technical Support

te.com/support-center

| | | | |
|----------------------|-----------------|--------------|--------------------|
| North America | +1 800 522 6752 | Asia Pacific | +86 400 820 6015 |
| North America (Toll) | +1 717 986 7777 | Japan | 044 844 8180 |
| EMEA/South Africa | +800 0440 5100 | Australia | +61 2 9554 2695 |
| EMEA (Toll) | +31 73 624 6999 | New Zealand | +64 (0) 9 634 4580 |
| India (Toll-Free) | +800 440 5100 | | |

te.com/38999

DEUTSCH, TE, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other products, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice.

Consult TE for the latest dimensions and design specifications.

© 2016 TE Connectivity Ltd. family of companies All Rights Reserved.

1-1773870-8 10/16