



second source devices
 produits seconde source



Type	V _{CEO} (V)	V _{CEX} (V)	I _C (sat) (A)	t _f max (μs)	Case
BUX 84	400	800	1	1,4	 TO-220 AB
BUX 85	450	1000	1	1,4	
MJE 13004	300	600	2	0,9	
MJE 13005	400	700	2	0,9	
MJE 13005 A	400	850	2	0,9	
MJE 13006	300	600	5	0,7	
MJE 13007	400	700	5	0,7	
MJE 13007 A	400	850	5	0,7	
MJE 13008	300	600	8	0,7	
MJE 13009	400	700	8	0,7	
MJE 13009 A	400	850	8	0,7	
BUX 80	400	800	5	0,8	 TO-3
BUX 81	450	1000	5	0,8	
BUW 34	400	500	5	0,8	
BUW 35	400	800	5	0,8	
BUW 36	450	900	5	0,8	
2N 6671	300	450	5	0,4	
2N 6672	350	550	5	0,4	
2N 6673	400	650	5	0,4	
2N 6674	300	450	10	0,5	
2N 6675	400	650	10	0,5	
2N 6676	300	450	15	0,5	
2N 6677	350	550	15	0,5	
2N 6678	400	650	15	0,5	
BUS 47	450	850	6	0,4	
BUS 48	450	850	10	0,4	
MJ 8504	700	1200	5	2	
MJ 8505	800	1400	5	2	

www.datasheetonline.com