



**Bay Linear**

Inspire the Linear Power

## 1.5A Positive Voltage Regulator

## LM78XX

### Description

The Bay Linear LM78XX is integrated linear positive regulator with three terminals. The LM78XX offer several fixed output voltages making them useful in wide range of applications. When used as a zener diode/resistor combination replacement, the LM78XX usually results in an effective output impedance improvement of two orders of magnitude, lower quiescent current.

The LM78XX is available in the TO-252, TO-220 & TO-263 packages,

### Features

- **Output Current of 1.5A**
- **Output Voltage Tolerance of 5%**
- **Internal thermal overload protection**
- **Internal Short-Circuit Limited**
- **No External Component**
- **Output Voltage 5.0V, 6V, 8V, 9V, 10V, 12V, 15V, 18V, 24V**
- **Offer in plastic TO-252, TO-220 & TO-263**
- **Direct Replacement for LM78XX**

### Applications


- **Post regulator for switching DC/DC converter**
- **Bias supply for analog circuits**

# Datasheet.Live

### Packaging Information



TO-263-3 (S)



Top View

1. Input
2. GND
3. Output

### Ordering Information

Device	Operating Voltage	Temp.
LM7805	7 to 20	0 to 125 °C
LM7806	8 to 20	0 to 125 °C
LM7808	10.5 to 23	0 to 125 °C
LM7809	11.5 to 24	0 to 125 °C
LM7810	12.5 to 25	0 to 125 °C
LM7812	14.5 to 27	0 to 125 °C
LM7815	17.5 to 30	0 to 125 °C
LM7818	20.5 to 33	0 to 125 °C
LM7824	26.5 to 39	0 to 125 °C

- TO-220 (T)  
TO-263 (S)  
TO-252 (D)

**Absolute Maximum Rating**

Parameter	LM78--	Unit
Input Voltage	LM7824, LM7827 All Others	40 35
Operating Free-Air, Case, Virtual Junction Temp.	0 to 150	°C
Storage Temperature Range	-65 to 150	
Lead temperature 1.6 mm from case for sec.	260	

**Electrical Characteristics (LM7805)**(V<sub>I</sub>=10V, I<sub>O</sub>=500mA, 0°C ≤ T<sub>J</sub> ≤ 125 °C, unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = 25 °C	4.8	5.0	5.2	V
Line Regulation	ΔV <sub>O</sub>	V <sub>I</sub> = 7V to 25V T <sub>J</sub> = 25 °C		3	100	mV
		V <sub>I</sub> = 8V to 12V T <sub>J</sub> = 25 °C		1	50	
Load Regulation	ΔV <sub>O</sub>	I <sub>O</sub> = 5mA to 1.5A, 25 °C		15	100	mV
		I <sub>O</sub> = 250mA to 750mA, 25 °C		5	50	
Ripple Rejection	RR	V <sub>I</sub> = 8V to 18V, f=120Hz	62	78		dB
Output Noise Voltage	V <sub>N</sub>	F= 10Hz to 100Hz T <sub>J</sub> = 25 °C		40		μV
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = 25 °C		2.0		V
Quiescent Current		T <sub>J</sub> = 25 °C		4.2	8	mA
Quiescent Current Change	ΔI <sub>Q</sub>	V <sub>I</sub> = 7V to 25V, T <sub>J</sub> = 25 °C			1.3	mA
		I <sub>O</sub> = 5mA to 1A, T <sub>J</sub> = 25 °C			0.5	

**Electrical Characteristics (LM7806)**(V<sub>I</sub>=11V, I<sub>O</sub>=500mA, 0°C ≤ T<sub>J</sub> ≤ 125 °C, unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = 25 °C	5.75	6.0	6.25	V
Line Regulation	ΔV <sub>O</sub>	V <sub>I</sub> = 8V to 25V T <sub>J</sub> = 25 °C		5	120	mV
		V <sub>I</sub> = 9V to 25V T <sub>J</sub> = 25 °C		1.5	60	
Load Regulation	ΔV <sub>O</sub>	I <sub>O</sub> = 5mA to 1.5A, 25 °C		14	120	mV
		I <sub>O</sub> = 250mA to 750mA, 25 °C		4	60	
Ripple Rejection	RR	V <sub>I</sub> = 9V to 19V, f=120Hz	59	75		dB
Output Noise Voltage	V <sub>N</sub>	F= 10Hz to 100Hz T <sub>J</sub> = 25 °C		45		μV
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = 25 °C		2.0		V
Quiescent Current		T <sub>J</sub> = 25 °C		4.3	8.0	mA
Quiescent Current Change	ΔI <sub>Q</sub>	V <sub>I</sub> = 8V to 25V, T <sub>J</sub> = 25 °C			1.3	mA
		I <sub>O</sub> = 5mA to 1A, T <sub>J</sub> = 25 °C			0.5	

## Electrical Characteristics (LM7808)

( $V_I=14V$ ,  $I_O=500mA$ ,  $0^\circ C \leq T_J \leq 125^\circ C$ , unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^\circ C$	7.7	8.0	8.3	V
Line Regulation	$\Delta V_O$	$V_I = 10.5V$ to $25V$ , $T_J = 25^\circ C$		6	160	mV
		$V_I = 11V$ to $17V$ , $T_J = 25^\circ C$		2	80	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^\circ C$		12	160	mV
		$I_O = 250mA$ to $750mA$ , $25^\circ C$		4	80	
Ripple Rejection	RR	$V_I = 11.5V$ to $21.5V$ , $f=120Hz$	55	72		dB
Output Noise Voltage	$V_N$	$F=10Hz$ to $100Hz$ , $T_J = 25^\circ C$		52		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^\circ C$		2.0		V
Quiescent Current		$T_J = 25^\circ C$		4.3	8	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 10.5V$ to $25V$ , $T_J = 25^\circ C$			1	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^\circ C$			0.5	

## Electrical Characteristics (LM7809)

( $V_I=16V$ ,  $I_O=500mA$ ,  $0^\circ C \leq T_J \leq 125^\circ C$ , unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^\circ C$	8.6	9.0	9.40	V
Line Regulation	$\Delta V_O$	$V_I = 11.5V$ to $27V$ , $T_J = 25^\circ C$		7	180	mV
		$V_I = 13V$ to $19V$ , $T_J = 25^\circ C$		2	90	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^\circ C$		12	180	mV
		$I_O = 250mA$ to $750mA$ , $25^\circ C$		4	90	
Ripple Rejection	RR	$V_I = 12V$ to $19V$ , $f=120Hz$	55	70		dB
Output Noise Voltage	$V_N$	$F=10Hz$ to $100Hz$ , $T_J = 25^\circ C$		60		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^\circ C$		2.0		V
Quiescent Current		$T_J = 25^\circ C$		4.3	8	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 11.5V$ to $27V$ , $T_J = 25^\circ C$			1.0	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^\circ C$			0.5	

**Electrical Characteristics (LM7810)**

( $V_I=17V$ ,  $I_O=500mA$ ,  $0^\circ C \leq T_J \leq 125^\circ C$ , , unless otherwise specified. (Note 1)

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^\circ C$	9.6	10	10.4	V
Line Regulation	$\Delta V_O$	$V_I = 12.5V$ to $28V$ $T_J = 25^\circ C$		7	200	mV
		$V_I = 14V$ to $20V$ $T_J = 25^\circ C$		2	100	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^\circ C$		12	200	mV
		$I_O = 250mA$ to $750mA$ , $25^\circ C$		4	100	
Ripple Rejection	RR	$V_I = 13V$ to $23V$ , $f=120Hz$	55	71		dB
Output Noise Voltage	$V_N$	$F= 10Hz$ to $100Hz$ $T_J = 25^\circ C$		70		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^\circ C$		2.0		V
Quiescent Current		$T_J = 25^\circ C$		4.3	8	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 12.5V$ to $28V$ , $T_J = 25^\circ C$			1.0	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^\circ C$			0.5	

**Electrical Characteristics (LM7812)**

( $V_I=19V$ ,  $I_O=500mA$ ,  $0^\circ C \leq T_J \leq 125^\circ C$ , unless otherwise specified. (Note 1)

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^\circ C$	11.50	12	12.5	V
Line Regulation	$\Delta V_O$	$V_I = 14.5V$ to $30V$ $T_J = 25^\circ C$		10	240	mV
		$V_I = 16V$ to $22V$ $T_J = 25^\circ C$		3.0	120	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^\circ C$		12	240	mV
		$I_O = 250mA$ to $750mA$ , $25^\circ C$		4	120	
Ripple Rejection	RR	$V_I = 15V$ to $25V$ , $f=120Hz$	55	71		dB
Output Noise Voltage	$V_N$	$F= 10Hz$ to $100Hz$ $T_J = 25^\circ C$		75		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^\circ C$		2.0		V
Quiescent Current		$T_J = 25^\circ C$		4.3	8.0	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 14.5V$ to $30V$ , $T_J = 25^\circ C$			1.0	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^\circ C$			0.5	

**Electrical Characteristics (LM7815)**

( $V_I=23V$ ,  $I_O=500mA$ ,  $0^\circ C \leq T_J \leq 125^\circ C$ , unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^\circ C$	14.40	15	15.60	V
Line Regulation	$\Delta V_O$	$V_I = 17.5V$ to $30V$ $T_J = 25^\circ C$		12	300	mV
		$V_I = 20V$ to $26V$ $T_J = 25^\circ C$		3	150	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^\circ C$		12	300	mV
		$I_O = 250mA$ to $750mA$ , $25^\circ C$		4	150	
Ripple Rejection	RR	$V_I = 18.5V$ to $28.5V$ , $f=120Hz$	54	70		dB
Output Noise Voltage	$V_N$	$F= 10Hz$ to $100Hz$ $T_J = 25^\circ C$		90		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^\circ C$		2.0		V
Quiescent Current		$T_J = 25^\circ C$		4.3	8.0	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 17.5V$ to $30V$ , $T_J = 25^\circ C$			1.0	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^\circ C$			0.5	

**Electrical Characteristics (LM7818)**

( $V_I=27V$ ,  $I_O=500mA$ ,  $0^\circ C \leq T_J \leq 125^\circ C$ , unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	$V_O$	$T_J = 25^\circ C$	17.30	18	18.7	V
Line Regulation	$\Delta V_O$	$V_I = 21V$ to $33V$ $T_J = 25^\circ C$		15	360	mV
		$V_I = 24V$ to $33V$ $T_J = 25^\circ C$		5	180	
Load Regulation	$\Delta V_O$	$I_O = 5mA$ to $1.5A$ , $25^\circ C$		12	360	mV
		$I_O = 250mA$ to $750mA$ , $25^\circ C$		4	180	
Ripple Rejection	RR	$V_I = 22V$ to $32V$ , $f=120Hz$	53	69		dB
Output Noise Voltage	$V_N$	$F= 10Hz$ to $100Hz$ $T_J = 25^\circ C$		110		$\mu V$
Dropout Voltage	$V_D$	$T_J = 25^\circ C$		2.0		V
Quiescent Current		$T_J = 25^\circ C$		4.5	8.0	mA
Quiescent Current Change	$\Delta I_Q$	$V_I = 21V$ to $33V$ , $T_J = 25^\circ C$			1.0	mA
		$I_O = 5mA$ to $1A$ , $T_J = 25^\circ C$			0.5	

**Electrical Characteristics (LM7824)**(V<sub>I</sub>=33V, I<sub>O</sub>=500mA, 0°C ≤ T<sub>J</sub> ≤ 125 °C, unless otherwise specified. (Note 1))

Parameter	Symbol	Conditions	MIN	TYP	MAX	UNIT
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = 25 °C	23	24	25	V
Line Regulation	ΔV <sub>O</sub>	V <sub>I</sub> = 27V to 38V T <sub>J</sub> = 25 °C		18	480	mV
		V <sub>I</sub> = 30V to 36V T <sub>J</sub> = 25 °C		6	240	
Load Regulation	ΔV <sub>O</sub>	I <sub>O</sub> = 5mA to 1.5A, 25 °C		12	480	mV
		I <sub>O</sub> = 250mA to 750mA, 25 °C		4	240	
Ripple Rejection	RR	V <sub>I</sub> = 28V to 38V, f = 120Hz	50	66		dB
Output Noise Voltage	V <sub>N</sub>	F = 10Hz to 100Hz T <sub>J</sub> = 25 °C		170		μV
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = 25 °C		2.0		V
Quiescent Current		T <sub>J</sub> = 25 °C		4.6	8.0	mA
Quiescent Current Change	ΔI <sub>Q</sub>	V <sub>I</sub> = 27V to 38V, T <sub>J</sub> = 25 °C			1.0	mA
		I <sub>O</sub> = 5mA to 1.0A, T <sub>J</sub> = 25 °C			0.5	

**Advance Information-** These data sheets contain descriptions of products that are in development. The specifications are based on the engineering calculations, computer simulations and/ or initial prototype evaluation.

**Preliminary Information-** These data sheets contain minimum and maximum specifications that are based on the initial device characterizations. These limits are subject to change upon the completion of the full characterization over the specified temperature and supply voltage ranges.

The application circuit examples are only to explain the representative applications of the devices and are not intended to guarantee any circuit design or permit any industrial property right to other rights to execute. Bay Linear takes no responsibility for any problems related to any industrial property right resulting from the use of the contents shown in the data book. Typical parameters can and do vary in different applications. Customer's technical experts must validate all operating parameters including "Typical" for each customer application.

---

**LIFE SUPPORT AND NUCLEAR POLICY**

Bay Linear products are not authorized for and should not be used within life support systems which are intended for surgical implants into the body to support or sustain life, in aircraft, space equipment, submarine, or nuclear facility applications without the specific written consent of Bay Linear President.

---