



Self-insulated with high dielectric-strength nylon sleeves, these ring terminals are recommended for temperatures up to 105°C. An inner bronze insulation grip sleeve lengthens the flexing radius of the conductor and eliminates conductor creep. The nylon jacket is color-coded:

Color Code	Wire Range
yellow	26-22
red	22-16
blue	18-14
yellow	12-10

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (12050 tool and application dies). See page C61.

Please put the suffix M for Mylar Tape RA2573M.

(Bulk number 1000 and 500 packages.)

RZ & RAX stock thickness: .02

RA & RB stock thickness: .03

RA stock thickness: .04

Nylon Insulated Ring—Insulation Grip

Cat. No.	Bulk Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Wt./lbs. Bolt Hole	Per 1000	Dimensions			
							A	B	C	M
RZ22-2**	—	100	26-22	.083	#2	1	.57	.14	.13	.49
RZ22-4**	—	100	26-22	.083	#4	1	.65	.21	.20	.54
RZ22-6**	—	100	26-22	.083	#6	1	.65	.21	.20	.54
RZ22-8**	—	100	26-22	.083	#8	1	.75	.25	.23	.62
RZ22-10**	—	100	26-22	.083	#10	1	.75	.25	.23	.62
—	RAX23*	1000	26-24	.125	#2	3	.66	.14	.14	.59
—	RAX43*	1000	26-24	.125	#4	3	.74	.20	.19	.64
—	RAX63*	1000	26-24	.125	#6	3	.84	.25	.22	.72
—	RAX83*	1000	26-24	.125	#8	3	.84	.25	.22	.72
—	RAX103*	1000	26-24	.125	#10	3	.84	.25	.24	.72
RA18-4	RA323	100/1M	22-16	.136	#4	2	.70	.23	.14	.59
—	RA333	1000	22-16	.136	#6	2	.70	.23	.14	.59
RA18-6	RA853	100/1M	22-16	.136	#6	2	.83	.26	.25	.71
RA18-8	RA833	100/1M	22-16	.136	#8	3	.83	.26	.25	.71
—	RA863	1000	22-16	.136	#8	3	.83	.26	.25	.71
RA18-10	RA873	100/1M	22-16	.136	#10	2	.86	.31	.25	.71
RA18-14	RA713	100/1M	22-16	.136	#10	2	.86	.31	.25	.71
RA18-516	RA723	100/1M	22-16	.136	5/16"	3	1.07	.46	.31	.84
RA18-38	RA733	100/1M	22-16	.136	3/8"	3	1.17	.53	.35	.87
RA18-12	RA753	100/1M	22-16	.136	1/2"	3	1.27	.72	.50	.92
RB14-4	RB1323	100/1M	18-14	.162	#4	2 1/2	.72	.26	.14	.59
RB14-6	RB853	100/1M	18-14	.162	#6	3	.89	.31	.25	.71
—	RB1333	1000	18-14	.162	#6	3	.74	.26	.14	.59
RB14-8	RB863	100/1M	18-14	.162	#8	3	.89	.31	.25	.71
RB14-10	RB873	100/1M	18-14	.162	#10	3 1/2	.89	.31	.25	.71
RB14-14	RB713	100/1M	18-14	.162	1/4"	3 1/2	1.08	.47	.31	.81
RB14-516	RB723	100/1M	18-14	.162	5/16"	3 1/2	1.08	.47	.31	.84
RB14-38	RB733	100/1M	18-14	.162	3/8"	3 1/2	1.17	.53	.35	.87
RB14-12	RB753	100/1M	18-14	.162	1/2"	4	1.25	.72	.50	.90
RC10-6	RC333	50/500	12-10	.210	#6	3	1.00	.37	.27	.81
RC10-8	RC863	50/500	12-10	.210	#8	5	1.00	.37	.27	.81
RC10-10	RC363	50/500	12-10	.210	#10	5	1.00	.37	.27	.81
RC10-14	RC713	50/500	12-10	.210	1/4"	6	1.12	.53	.32	.86
RC10-516	RC703	50/500	12-10	.210	5/16"	6	1.21	.53	.31	.94
RC10-38	RC733	50/500	12-10	.210	3/8"	6	1.27	.59	.35	.98
RC10-12	RC753	50/500	12-10	.210	1/2"	6	1.37	.72	.52	1.02

* Not Listed by U.L. CSA

** CSA Listed only

U.L. Listed E-9809

Installing tools: WT2000, WT112M, WT145C, WT1455, ERG-2001, ERG-2003, WT145A, WT2130A (RC,RBC)

Installing tool: WT1452 (RZ series only)

For Mil Specs listing, please refer to page C73.