

TYPE	MATERIAL	POLARITY	REPLACE- MENT	PAGE NUMBER	USE	MAXIMUM RATINGS						ELECTRICAL CHARACTERISTICS											
						P _D @ 25°C	P _{Point} Ref	T _J °C	V _{CB} (volts)	V _{CE--} (volts)	Subscript	h _{FE} @ I _C		V _{CE(SAT)} @ I _C		h _{FE}	Subscript	f _T Units	Subscript				
												(min)	(max)	Units	(volts)					Units			
2N992	G	P	2N3250 2N3248	8-61 8-208 8-204	RFC	67M	A	75	20	20	R	40		1.0M		40	E						
2N993	G	P			RFC	67M	A	75	20	20	R	40		1.0M		40	E						
2N994	G	P			HSS	200M	A	150	15	6.0	0	45	140	10M	0.18	10M							
2N995	S	P			RFA	360M	A	200	20	15	0	35	140	20M	0.2	20M					100M	T	
2N995A	S	P			RFA	360M	A	200	20	15	0	35	140	20M	0.2	20M					100M	T	
2N996	S	P			RFA	360M	A	200	15	12	0	35		20M	0.3	60M					100M	T	
2N997	S	N			AFA	500M	A	175	75	40	0	35		100*	1.6	50M		1000	E				
2N998	S	N			SPP	500M	A	200	100	60	0				1.2	100M							
2N999	S	N			SPP	500M	A	200	60	60	0				1.6	100M							
2N1000	G	P			MSA	150M	A	100	40	25	0			40	10M	0.25	100M					7.0M	E
2N1002	G	P			RFA	120M	A	100	35	20	0							10	E				
2N1004	G	P			WID	120M	A	100	35	20	0						10	E					
2N1005	S	N			AFA	150M	A	175	15	15	0	10	25	10M	0.6	10M							
2N1006	S	N			AFA	150M	A	175	15	15	0	25	150	10M	0.6	10M							
2N1007	G	P	LPA	35W	C	95	25	20	0	50	250	1.0A	1.0	2.0A					60K	T			
2N1008	G	P	AFA	0.3W	C	85	20	15	R				0.25	0.1A									
2N1008A	G	P	AFA	0.3W	C	85	40	35	R				0.25	0.1A									
2N1008B	G	P	AFA	0.3W	C	85	60	55	R				0.25	0.1A									
2N1009	G	P	AFA	0.4W	C	85	35	35	R				0.25	0.1A									
2N1010	G	N	APC	20M	A	55	10	10	0														
2N1011	G	P	LPA	35W	C	95	80	80	S	30	75	3.0A	1.5	3.0A		20	E		5.0K	E			
2N1012	G	N	MSA	150M	A	100	40	25	0	20		100M	0.2	100M					3.0M	E			
2N1014	G	P	LPA	50M	A	100	100	65	0	40	50	4.0A	0.8	4.0A					0.5M	E			
2N1015	S	N	PMS	150W	C	150	30	30	V	10		2.0A	1.5	2.0A									
2N1015A	S	N	PMS	150W	C	150	60	60	V	10		2.0A	1.5	2.0A									
2N1015B	S	N	PMS	150W	C	150	100	100	V	10		2.0A	1.5	2.0A									
2N1015C	S	N	PMS	150W	C	150	150	150	V	10		2.0A	1.5	2.0A									
2N1015D	S	N	PMS	150W	C	150	200	200	V	10		2.0A	1.5	2.0A									
2N1015E	S	N	PMS	150W	C	150	250	250	V	10		2.0A	1.5	2.0A									
2N1015F	S	N	PMS	150W	C	150	300	300	V	10		2.0A	1.5	2.0A									
2N1016	S	N	PMS	150W	C	150	30	30	V	10		5.0A	2.5	5.0A									
2N1016A	S	N	PMS	150W	C	150	60	60	V	10		5.0A	2.5	5.0A									
2N1016B	S	N	PMS	150W	C	150	100	100	V	10		5.0A	2.5	5.0A									
2N1016C	S	N	PMS	150W	C	150	150	150	V	10		5.0A	2.5	5.0A									
2N1016D	S	N	PMS	150W	C	150	200	200	V	10		5.0A	2.5	5.0A									
2N1016E	S	N	PMS	150W	C	150	250	250	V	10		5.0A	2.5	5.0A									
2N1016F	S	N	PMS	150W	C	150	300	300	V	10		5.0A	2.5	5.0A									
2N1017	G	P	MSA	150M	A	85	30	10	0	70		20M	2.6	200M					15M	B			
2N1018	G	P	MSS	200M	A	100	30	6.0	0	70		70M	2.6	200M					20M	B			
2N1021	G	P	LPA	50W	C	95	100	100	X	23	70	1.0A	1.0	5.0A									
2N1021A	G	P	LPA	150W	C	100	100	30	V	30	90	5.0A	0.5	5.0A					200K	T			
2N1022	G	P	LPA	50W	C	95	120	120	X	23	70	5.0A	1.0	5.0A									
2N1022A	G	P	LPA	150W	C	100	120	55	0	30	90	5.0A	0.5	5.0A					200K	T			
2N1023	G	P	RFA	120M	A	100	40	40	0	20	175	1.5M											
2N1024	S	P	AFA	0.25W	A	175	18	15	U							9.0	E		1.0M	B			
2N1025	S	P	AFA	0.25W	A	175	40	35	U							9.0	E		1.0M	B			
2N1026	S	P	AFA	0.25W	A	175	40	35	U							18	E		2.0M	B			
2N1027	S	P	AFA	0.25W	A	175	18	15	U							18	E		4.0M	B			
2N1028	S	P	AFA	0.25W	A	175	12	10	U							9.0	E		7.2M	T			
2N1029	G	P	LPA	90W	C	100	50	20	0	20	60	10A	1.0	10A									
2N1029A	G	P	LPA	90W	C	100	60	30	0	20	60	10A	1.0	10A									
2N1029B	G	P	LPA	90W	C	100	90	60	0	20	60	10A	1.0	10A									
2N1029C	G	P	LPA	90W	C	100	100	70	0	20	60	10A	1.0	10A									
2N1030	G	P	LPA	90W	C	100	50	20	0	50	100	10A	1.0	10A									
2N1030A	G	P	LPA	90W	C	100	60	30	0	50	100	10A	1.0	10A									
2N1030B	G	P	LPA	90W	C	100	90	60	0	50	100	10A	1.0	10A									
2N1030C	G	P	LPA	90W	C	100	100	70	0	50	100	10A	1.0	10A									
2N1031	G	P	LPA	90W	C	100	50	30	S	20	60	10A	1.0	10A					2.0K	E			
2N1031A	G	P	LPA	90W	C	100	60	40	S	20	60	10A	1.0	10A					2.0K	E			
2N1031B	G	P	LPA	90W	C	100	90	70	S	20	60	10A	1.0	10A					2.0K	E			
2N1031C	G	P	LPA	90W	C	100	100	80	S	20	60	10A	1.0	10A									
2N1032	G	P	LPA	90W	C	100	50	30	S	50	100	10A	1.0	10A					25	E			
2N1032A	G	P	LPA	90W	C	100	60	40	S	50	100	10A	1.0	10A					25	E			
2N1032B	G	P	LPA	90W	C	100	90	70	S	50	100	10A	1.0	10A					25	E			
2N1032C	G	P	LPA	90W	C	100	100	80	S	50	100	10A	1.0	10A					25	E			
2N1034	S	P	AFA	250M	A	160	50	40	0				0.5	8.0M		9.0	E		150K	B			
2N1035	S	P	AFA	250M	A	160	50	35	0				0.4	8.0M		18	E		200K	B			
2N1036	S	P	AFA	250M	A	160	50	30	0				0.3	8.0M		34	E		300K	B			
2N1037	S	P	AFA	250M	A	160	50	35	0				0.5	8.0M		9.0	E		150K	B			
2N1038	G	P	LPA	20W	C	95	40	40	V	20	60	1.0A	0.25	1.0A					8.0K	E			
2N1039	G	P	LPA	20W	C	95	60	60	V	20	60	1.0A	0.25	1.0A					8.0K	E			
2N1040	G	P	LPA	20W	C	95	80	80	V	20	60	1.0A	0.25	1.0A					8.0K	E			
2N1041	G	P	LPA	20W	C	95	100	100	V	20	60	1.0A	0.25	1.0A		18	E		8.0K	E			
2N1042	G	P	LPA	20W	C	100	40	40	V	20	60	3.0A	0.75	3.0A		2.0	E		250K	T			
2N1043	G																						