

TYPE	MATERIAL	POLARITY	REPLACE- MENT	PAGE NUMBER	USE	MAXIMUM RATINGS					ELECTRICAL CHARACTERISTICS										
						P _D @ 25°C	T _J °C	V _{CB} (volts)	V _{CE} — (volts)	Subscript	h _{FE} @ I _C		V _{CE(SAT)} @ I _C		h _{FE}	Subscript	f _m	Subscript			
											(min)	(max)	Units	(volts)	Units			Units	Units		
2N3174	S	P	2N3790	7-147	HPA	75W	C	200	100	100	0	12	36	1.0A	0.75	1.0A	10	E	1.0M	T	
2N3175	S	P	MJ2267	7-202	HPA	85W	C	200	40	40	0	10	30	2.0A	1.0	2.0A	10	E	1.0M	T	
2N3176	S	P	2N3789	7-147	HPA	85W	C	200	60	60	0	10	30	2.0A	1.0	2.0A	10	E	1.0M	T	
2N3177	S	P	2N3790	7-147	HPA	85W	C	200	80	80	0	10	30	2.0A	1.0	2.0A	10	E	1.0M	T	
2N3178	S	P	2N3790	7-147	HPA	85W	C	200	100	100	0	10	30	2.0A	1.0	2.0A	10	E	1.0M	T	
2N3179	S	P	MJ2267	7-202	HPA	85W	C	200	40	40	0	10	30	2.0A	1.0	2.0A	10	E	1.0M	T	
2N3180	S	P	2N3789	7-147	HPA	85W	C	200	60	60	0	10	30	2.0A	1.0	2.0A	10	E	1.0M	T	
2N3181	S	P	2N3790	7-147	HPA	85W	C	200	80	80	0	10	30	2.0A	1.0	2.0A	10	E	1.0M	T	
2N3182	S	P	2N3790	7-147	HPA	85W	C	200	100	100	0	10	30	2.0A	1.0	2.0A	10	E	1.0M	T	
2N3183	S	P	2N3789	7-147	HPA	75W	C	200	40	40	0	10	30	2.0A	1.0	2.0A	10	E	1.0M	T	
2N3184	S	P	2N3789	7-147	HPA	75W	C	200	60	60	0	10	30	2.0A	1.0	2.0A	10	E	1.0M	T	
2N3185	S	P	2N3790	7-147	HPA	75W	C	200	80	80	0	10	30	2.0A	1.0	2.0A	10	E	1.0M	T	
2N3186	S	P	2N3790	7-147	HPA	75W	C	200	100	100	0	10	30	2.0A	1.0	2.0A	10	E	1.0M	T	
2N3187	S	P	MJ2267	7-202	HPA	85W	C	200	40	40	0	10	30	3.0A	0.9	3.0A	10	E	1.0M	T	
2N3188	S	P	2N3789	7-147	HPA	85W	C	200	60	60	0	10	30	3.0A	0.9	3.0A	10	E	1.0M	T	
2N3189	S	P	2N3790	7-147	HPA	85W	C	200	80	80	0	10	30	3.0A	0.9	3.0A	10	E	1.0M	T	
2N3190	S	P	2N3790	7-147	HPA	85W	C	200	100	100	0	10	30	3.0A	0.9	3.0A	10	E	1.0M	T	
2N3191	S	P	2N3790	7-147	HPA	85W	C	200	40	40	0	10	30	3.0A	0.9	3.0A	10	E	1.0M	T	
2N3192	S	P	2N3789	7-147	HPA	85W	C	200	60	60	0	10	30	3.0A	0.9	3.0A	10	E	1.0M	T	
2N3193	S	P	2N3790	7-147	HPA	85W	C	200	80	80	0	10	30	3.0A	0.9	3.0A	10	E	1.0M	T	
2N3194	S	P	2N3790	7-147	HPA	85W	C	200	100	100	0	10	30	3.0A	0.9	3.0A	10	E	1.0M	T	
2N3195	S	P	2N3790	7-147	HPA	75W	C	200	40	40	0	10	30	3.0A	0.9	3.0A	10	E	1.0M	T	
2N3196	S	P	2N3789	7-147	HPA	75W	C	200	60	60	0	10	30	3.0A	0.9	3.0A	10	E	1.0M	T	
2N3197	S	P	2N3790	7-147	HPA	75W	C	200	80	80	0	10	30	3.0A	0.9	3.0A	10	E	1.0M	T	
2N3198	S	P	2N3790	7-147	HPA	75W	C	200	100	100	0	10	30	3.0A	0.9	3.0A	10	E	1.0M	T	
2N3199	S	P	2N3790	7-147	HPA	40W	C	200	40	40	0	20	60	1.0A	0.3	1.0A	10	E	1.0M	T	
2N3200	S	P	2N3740	7-137	HPA	40W	C	200	60	60	0	20	60	1.0A	0.3	1.0A	10	E	1.0M	T	
2N3201	S	P	2N3741	7-137	HPA	40W	C	200	80	80	0	20	60	1.0A	0.3	1.0A	10	E	1.0M	T	
2N3202	S	P	2N3741	7-137	HPA	8.8W	C	200	40	40	0	20	60	1.0A	0.3	1.0A	10	E	1.0M	T	
2N3203	S	P	2N3740	7-137	HPA	8.8W	C	200	60	60	0	20	60	1.0A	0.3	1.0A	10	E	1.0M	T	
2N3204	S	P	2N3741	7-137	HPA	8.8W	C	200	80	80	0	20	60	1.0A	0.3	1.0A	10	E	1.0M	T	
2N3205	S	P	2N3741	7-137	HPA	40W	C	200	40	40	0	20	60	0.5A	0.4	0.5A	10	E	1.0M	T	
2N3206	S	P	2N3740	7-137	HPA	40W	C	200	60	60	0	20	60	0.5A	0.4	0.5A	10	E	1.0M	T	
2N3207	S	P	2N3741	7-137	HPA	40W	C	200	100	100	0	20	60	0.5A	0.4	0.5A	10	E	1.0M	T	
2N3208	S	P	2N3740	7-137	HPA	8.8W	C	200	40	40	0	20	60	0.5A	0.4	0.5A	10	E	1.0M	T	
2N3209	S	P	MM2894	8-328	MSS	0.36W	A	200	20	20	0	30	120	30M	0.2	30M	10	E	400M	T	
2N3210	S	N		8-196	HSS	0.36W	A	200	40	15	0	30	120	10M	0.75	0.2A	300M	T			
2N3211	S	N		8-198	HSS	0.36W	A	200	40	15	0	50	150	10M	0.2	10M	350M	T			
2N3212	S	N			LPA	14W	C	110	100	80	0	30	90	3.0A	0.5	5.0A	3.0	E			
2N3213	G	P			LPA	14W	C	110	80	60	0	30	90	3.0A	0.5	5.0A	3.0	E			
2N3214	G	P			LPA	14W	C	110	60	40	0	30	90	3.0A	0.5	5.0A	3.0	E			
2N3215	G	P			LPA	14W	C	110	40	30	0	30	90	3.0A	0.5	5.0A	3.0	E			
2N3216	G	P			MSS	150M	A	100	20	10	0	60	100	200M	0.22	200M			10M	T	
2N3217	S	P			CHP	400M	A	200	15	10	0								1.0M	T	
2N3218	S	P			CHP	400M	A	200	25	20	0								1.0M	T	
2N3219	S	P			CHP	400M	A	200	40	35	0								1.0M	T	
2N3220	S	N			HFA	6.0W	C	175	100	80	0	20	60	1.0A	1.25	1.0A	20	E	10M	T	
2N3221	S	N			HPA	6.0W	C	175	100	80	0	40	120	1.0A	1.25	1.0A	40	E	10M	T	
2N3222	S	N			HPA	6.0W	C	175	80	60	0	20	60	1.0A	1.25	1.0A	20	E	10M	T	
2N3223	S	N			HPA	6.0W	C	175	80	60	0	40	120	1.0A	1.25	1.0A	40	E	10M	T	
2N3224	S	P	2N3498	8-232	VID	0.7W	A	200	100	100	0	20	60	50M			20	E	60M	T	
2N3225	S	P	2N3498	8-232	VID	0.7W	A	200	100	100	0	40	120	50M			40	E	80M	T	
2N3226	S	N			LPA	75W	C	200	35	35	0	20	50	2.0A	1.2	2.7A	20	E	30K	T	
2N3227	S	N		8-130	HSS	0.36W	A	200	40	20	0	100	300	10M	0.25	10M			500M	T	
2N3228	Thyristor, see Table on Page 1-154																				
2N3229	S	N			HPA	17.5W	C	200	105	60	0	5.0	20K	2.5A	1.0	2.5A			150M	T	
2N3230	S	N			PHS	25W	C	200	80	60	0	2K	20K	2.0A	1.4	2.0A			40M	T	
2N3231	S	N			PHS	25W	C	200	100	80	0	2K	20K	2.0A	1.4	2.0A			40M	T	
2N3232	S	N			HPA	117W	C	200	80	60	0	18	55	3.0A	2.5	3.0A	10	E	1.0M	T	
2N3233	S	N		7-106	HPA	117W	C	200	110	100	0	18	55	3.0A	2.5	3.0A	10	E	1.0M	T	
2N3234	S	N			HPA	117W	C	200	160	160	0	18	55	3.0A	2.5	3.0A	10	E	1.0M	T	
2N3235	S	N		7-106	HPA	117W	C	200	65	55	0	20	70	4.0A	1.1	4.0A	10	E	1.0M	T	
2N3236	S	N			HPA	150W	C	200	90	90	0	17	60	5.0A	1.1	5.0A	10	E	1.0M	T	
2N3237	S	N			HPA	200W	C	200	90	75	0	12	36	10A	2.0	10A	10	E	1.0M	T	
2N3238	S	N			HPA	150W	C	200	80	80	0	8.5	25	10A	3.0	10A	10	E	1.0M	T	
2N3239	S	N			HPA	150W	C	200	80	80	0	8.5	25	10A	1.0	10A	10	E	1.0M	T	
2N3240	S	N			HPA	150W	C	200	160	160	0	8.5	25	10A	1.0	10A	10	E	1.0M	T	
2N3241																					

GENERAL PURPOSE SWITCHING AND AMPLIFIER TRANSISTORS (SILICON)


Current versus Voltage

BV _{CEO} Min Volts	OPTIMUM COLLECTOR CURRENT									
	0 to 10 mA		10 mA to 100 mA		100 mA to 500 mA		500 mA to 1.0 A		1.0 A to 3.0 A	
	NPN	PNP	NPN	PNP	NPN	PNP	NPN	PNP	NPN	PNP
15 ↓ 29	2N916 2N2330 2N2331		2N916 2N1983 2N1984		2N696 2N697 2N718 2N1420 2N2195	2N1991				
30 ↓ 39			2N2218 2N2219 2N2221 2N2222	2N3133 2N3134 2N3135 2N3136	2N2218 2N2219 2N2221 2N2222 2N3299 2N3300 2N3301 2N3302	2N2800 2N2801 2N2837 2N2838 2N3133 2N3134 2N3135 2N3136				
49 ↓ 59	2N758 2N795 2N760 2N915 2N929 2N930 2N3946 2N3947	2N3250 2N3251 MM4048	2N2218A 2N2219A 2N2221A 2N2222A 2N2224 2N3946 2N3947	2N3250 2N3251	2N2194 2N2218A 2N2219A 2N2221A 2N2222A	2N2904 2N2905 2N2906 2N2907 2N3485 2N3486 2N4890	2N3192 2N3193	2N3244 2N3245	2N3506 2N3507	
60 ↓ 79	2N758A 2N759A 2N760A 2N929A 2N930A MM2483 MM2484	2N3798 2N3799 2N3250A 2N3251A	2N910 2N911 2N1990	2N3250A 2N3251A	2N656 2N699	2N2904A 2N2905A 2N2906A 2N2907A 2N3485A 2N3486A				
80 ↓ 99	2N739 2N740	2N3494 2N3496	2N720A 2N1893 2N2405	2N3494 2N3496	2N720A 2N3019 2N3020		2N3019 2N3020			
100 ↓ 149	2N4924	2N3495 2N3497 2N4928	2N3498 2N3499 2N4924	2N3495 2N3497 2N3634 2N3635 2N4928	2N3498 2N3499 2N4924	2N3634 2N3635				
150 ↓ 249	2N3114 2N4925 2N4926	2N4929 2N4930	2N3500 2N3501 2N4925 2N4926	2N3635 2N3637 2N4929 2N4930	2N3500 2N3501 2N4925	2N3636 2N3637				
250 UP	2N3742 2N4927	2N3743 2N4931	2N3742 2N4927	2N3743 2N4931						


2N3227 (SILICON)

For Specifications, See 2N2369 Data Sheet

2N3244 (SILICON) 2N3245



$V_{CEO} = 40-50 \text{ V}$
 $I_C = 1 \text{ A}$
 $f_T = 150-175 \text{ MHz}$



CASE 31
(TO-5)

PNP silicon annular transistors for medium-current, high-speed switching and driver applications.

Collector connected to case

MAXIMUM RATINGS

Rating	Symbol	2N 3244	2N 3245	Unit
Collector-Base Voltage	V_{CB}	40	50	Vdc
Collector-Emitter Voltage	V_{CEO}	40	50	Vdc
Emitter-Base Voltage	V_{EB}	5		Vdc
Collector Current	I_C	1		Adc
Total Device Dissipation @ 25° C Ambient Temperature Derating Factor Above 25° C	P_D	1.0 5.71		Watt mW/°C
Total Device Dissipation @ 25° C Case Temperature Derating Factor Above 25° C	P_D	5 28.6		Watts mW/°C
Junction Temperature, Operating	T_J	+200		°C
Storage Temperature Range	T_{stg}	-65 to +200		°C
Thermal Resistance	θ_{JA} θ_{JC}	0.175 35		°C/mW °C/W

2N3244, 2N3245 (Continued)

ELECTRICAL CHARACTERISTICS (at $T_A = 25^\circ\text{C}$ unless otherwise specified)

Characteristic	Fig. No.	Symbol	Min	Max	Unit	
Collector Cutoff Current ($V_{CB} = 30 \text{ Vdc}$, $I_E = 0$) ($V_{CB} = 30 \text{ Vdc}$, $I_E = 0$, $T_A = 100^\circ\text{C}$)		I_{CBO}	— —	.050 10	μAdc	
Collector Cutoff Current ($V_{CE} = 30 \text{ Vdc}$, $V_{BE(\text{off})} = 3 \text{ Vdc}$)		I_{CEX}	—	50	nAdc	
Emitter-Base Leakage Current ($V_{EB} = 3 \text{ Vdc}$, $I_C = 0$)		I_{EBO}	—	30	nAdc	
Base Cutoff Current ($V_{CE} = 30 \text{ Vdc}$, $V_{BE(\text{off})} = 3 \text{ Vdc}$)		I_{BL}	—	80	nAdc	
Collector-Base Breakdown Voltage ($I_C = 10 \mu\text{Adc}$, $I_E = 0$)	2N3244 2N3245	BV_{CBO}	40 50	— —	Vdc	
Collector-Emitter Breakdown Voltage* ($I_C = 10 \text{ mAdc}$, $I_B = 0$)	2N3244 2N3245	BV_{CEO}^*	40 50	— —	Vdc	
Emitter-Base Breakdown Voltage ($I_E = 10 \mu\text{Adc}$, $I_C = 0$)		BV_{EBO}	5	—	Vdc	
Collector Saturation Voltage* ($I_C = 150 \text{ mAdc}$, $I_B = 15 \text{ mAdc}$) ($I_C = 500 \text{ mAdc}$, $I_B = 50 \text{ mAdc}$) ($I_C = 1 \text{ Adc}$, $I_B = 100 \text{ mAdc}$)	2N3244 2N3245 2N3244 2N3245 2N3244 2N3245	$V_{CE(\text{sat})}^*$	— — — — —	0.3 0.35 0.5 0.6 1.0 1.2	Vdc	
Base-Emitter Saturation Voltage* ($I_C = 150 \text{ mAdc}$, $I_B = 15 \text{ mAdc}$) ($I_C = 500 \text{ mAdc}$, $I_B = 50 \text{ mAdc}$) ($I_C = 1 \text{ Adc}$, $I_B = 100 \text{ mAdc}$)		$V_{BE(\text{sat})}^*$	— 0.75 —	1.1 1.5 2.0	Vdc	
DC Forward Current Transfer Ratio* ($I_C = 150 \text{ mAdc}$, $V_{CE} = 1.0 \text{ Vdc}$) ($I_C = 500 \text{ mAdc}$, $V_{CE} = 1.0 \text{ Vdc}$) ($I_C = 1 \text{ Adc}$, $V_{CE} = 5 \text{ Vdc}$)	2N3244 2N3245 2N3244 2N3245 2N3244 2N3245	h_{FE}^*	60 35 50 30 25 20	— — 150 90 — —	—	
Output Capacitance ($V_{CB} = 10 \text{ Vdc}$, $I_E = 0$, $f = 100 \text{ kHz}$)	5	C_{ob}	—	25	pF	
Input Capacitance ($V_{OB} = 0.5 \text{ Vdc}$, $I_C = 0$, $f = 100 \text{ kHz}$)	5	C_{ib}	—	100	pF	
Current-Gain - Bandwidth Product ($I_C = 50 \text{ mAdc}$, $V_{CE} = 10 \text{ Vdc}$, $f = 100 \text{ MHz}$)	2N3244 2N3245	f_r	175 150	— —	MHz	
Delay Time Rise Time	($I_C = 500 \text{ mA}$, $I_{B1} = 50 \text{ mA}$ $V_{OB} = 2 \text{ V}$, $V_{CC} = 30 \text{ V}$) 2N3244 2N3245	t_d t_r	— —	15	ns	
Storage Time Fall Time				2N3244 2N3245	6,9	t_s t_f
Total Control Charge ($I_C = 500 \text{ mA}$, $I_B = 50 \text{ mA}$, $V_{CC} = 30 \text{ V}$)	2N3244 2N3245	7,10	Q_T			

* Pulse Test: $PW \leq 300 \mu\text{s}$, Duty Cycle $\leq 2\%$

2N3244, 2N3245 (Continued)

FIGURE 1 — MINIMUM CURRENT GAIN CHARACTERISTICS






FIGURE 2 — COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS



2N3244, 2N3245 (Continued)

FIGURE 3 — MAXIMUM SATURATION VOLTAGES




FIGURE 4 — TYPICAL TEMPERATURE COEFFICIENTS




FIGURE 5 — JUNCTION CAPACITANCE




FIGURE 6 — TYPICAL SWITCHING TIMES




FIGURE 7 — CHARGE DATA




FIGURE 8 — TURN-ON EQUIVALENT TEST CIRCUIT




FIGURE 9 — TURN-OFF EQUIVALENT TEST CIRCUIT




FIGURE 10 — Q_r TEST CIRCUIT




FIGURE 11 — TURN-OFF WAVEFORM

