



**FRONTIER
ELECTRONICS CO., LTD.**

500mW ZENER DIODE


**1N5221B
THRU
1N5257B**

FEATURES

- LOW COST
- SMALL SIZE
- GLASS SEALED

MECHANICAL DATA

- CASE : GLASS CASE
- TERMINALS : AXIAL LEADS, SOLDERABLE PER MIL-STD -202, METHOD 208
- POLARITY : COLOR BAND DENOTES CATHODE
- MOUNTING POSITION : ANY
- WEIGHT : 0.13 GRAMS



DO-35
(GLASS CASE)

DIMENSIONS IN INCHES AND (MILLIMETERS)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS
 RATINGS AT 25°C AMBIENT TEMPERATURE UNLESS OTHERWISE SPECIFIED
 STORAGE AND OPERATING TEMPERATURE RANGE -55 TO + 175°C

ELECTRICAL CHARACTERISTICS (TA=25°C UNLESS OTHERWISE NOTED) VF=1.2V MAX, IF = 200mA FOR ALL TYPES

JEDEC TYPE NO	NOMINAL ZENER VOLTAGE V _Z @ I _{ZT} *	TEST CURRENT I _{ZT}	MAXIMUM ZENER IMPEDANCE		TYPICAL TEMPERATURE COEFFICIENT	MAXIMUM REVERSE LEAKAGE CURRENT		MAXIMUM REGULATOR CURRENT I _{ZM}
			Z _{ZT} @ I _{ZT}	Z _{ZK} AT I _{ZK} =0.25mA		IR	TEST VOLTAGE SUFFIX B	
	VOLTS	mA	OHMS	OHMS	% / °C	µA	VOLTAGE	mA
1N5221B	2.4	20	30	1200	-0.085	100	1.0	191
1N5222B	2.5	20	30	1250	-0.085	100	1.0	182
1N5223B	2.7	20	30	1300	-0.080	75	1.0	168
1N5224B	2.8	20	30	1400	-0.080	75	1.0	162
1N5225B	3.0	20	29	1600	-0.075	50	1.0	151
1N5226B	3.3	20	28	1600	-0.070	25	1.0	138
1N5227B	3.6	20	24	1700	-0.065	15	1.0	126
1N5228B	3.9	20	23	1900	-0.060	10	1.0	115
1N5229B	4.3	20	22	2000	+0.055	5	1.0	106
1N5230B	4.7	20	19	1900	±0.030	5	2.0	97
1N5231B	5.1	20	17	1600	±0.030	5	2.0	89
1N5232B	5.6	20	11	1600	+0.038	5	3.0	81
1N5233B	6.0	20	7	1600	+0.038	5	3.5	76
1N5234B	6.2	20	7	1000	+0.045	5	4.0	73
1N5235B	6.8	20	5	750	+0.050	3	5.0	67
1N5236B	7.5	20	6	500	+0.058	3	6.0	61
1N5237B	8.2	20	8	500	+0.062	3	6.5	55
1N5238B	8.7	20	8	600	+0.065	3	6.5	52
1N5239B	9.1	20	10	600	+0.068	3	7.0	50
1N5240B	10	20	17	600	+0.075	3	8.0	45
1N5241B	11	20	22	600	+0.076	2	8.4	41
1N5242B	12	20	30	600	+0.077	1	9.1	38
1N5243B	13	9.5	13	600	+0.079	0.5	9.9	35
1N5244B	14	9.0	15	600	+0.082	0.1	10	32
1N5245B	15	8.5	16	600	+0.082	0.1	11	30
1N5246B	16	7.8	17	600	+0.083	0.1	12	28
1N5247B	17	7.4	19	600	+0.084	0.1	13	27
1N5248B	18	7.0	21	600	+0.085	0.1	14	25
1N5249B	19	6.6	23	600	+0.086	0.1	14	24
1N5250B	20	6.2	25	600	+0.086	0.1	15	23
1N5251B	22	5.6	29	600	+0.087	0.1	17	21.2
1N5252B	24	5.2	33	600	+0.087	0.1	18	19.1
1N5253B	25	5.0	35	600	+0.089	0.1	19	18.2
1N5254B	27	4.6	41	600	+0.090	0.1	21	16.8
1N5255B	28	4.5	44	600	+0.091	0.1	21	16.2
1N5256B	30	4.2	49	600	+0.091	0.1	23	15.1
1N5257B	33	3.8	58	700	+0.092	0.1	25	13.8

NOTE: SUFFIX "B" FOR ±5% ★ MEASURD WITH PULSE T_P=40ms

RATINGS AND CHARACTERISTIC CURVES 1N5221B THRU 1N5257B

FIG.1- BREAKDOWN CHARACTERISTICS




FIG.2- POWER ,TEMPERATURE DERATING CURVE

