





Rectifiers, General Purpose

1.0 to 250 Amperes

50 to 1600 Volts

IO (AMPS)	1.0				
@ TA (°C)	75	75	75	55	100
IFSM (AMPS)	30	50	50	50	50
					
CASE	GPR-1A	DO-41*		GPR-1A	DO-41 Glass
VRRM (VOLTS)					
50		1N4001	1N4001GPP**		
100		1N4002	1N4002GPP**		
200	1N3611	1N4003	1N4003GPP**	1N4245	1N4383
400	1N3612	1N4004	1N4004GPP**	1N4246	1N4384
600	1N3613	1N4005	1N4005GPP**	1N4247	1N4385
800	1N3614	1N4006	1N4006GPP**	1N4248	1N4585
1000	1N3957	1N4007	1N4007GPP**	1N4249	1N4586

V _F MAX @ I _F = I _O	1.1V	1.1V	1.1V	1.2V	1.1V
--	------	------	------	------	------

I _R MAX @ V _{RRM}	1.0μA	5.0μA	5.0μA	1.0μA	10μA
---------------------------------------	-------	-------	-------	-------	------

* Also available in DO-41SP Case (0.6mm lead diameter) with Radial Tape and Reel (DO-41SP-RPCU). See page 239.

** Device utilizes glass passivated chip for high reliability.