

Product data sheet

Characteristics

TVS6HWA10X

Surge Protect - HWA - 100kA - 240VAC delta -
3P3W - T4X

Product availability : Stock - Normally stocked in distribution facility



Price* : 3,606.00 USD



Datasheet.Live

Main

Product	Surge protection device
Range	Surgelogic
Device Short Name	HWA

Complementary

Surge Current	100 kA per phase
System Voltage	240 V delta AC
Phase	3 phases
Wiring Configuration	3-wire
Connection	Wire phase and neutral AWG 10 copper Wire ground AWG 10 copper Wire dry contacts AWG 22 copper
MCOV	300 V
Nominal Discharge Current	20 kA
Max Number of Poles	1
SCCR	200 kA
Local Signalling	Status LED, green = normal operation per phase Status LED, red = fault per phase Alarm = fault
Mounting Location	Bottom of enclosure
Device Mounting	Surface Flush with fixing kit
Height	4.8 in (122 mm)
Width	8.62 in (219 mm)
Depth	3.11 in (79 mm)

Environment

Enclosure Rating	NEMA 4X
Enclosure Material	Plastic, colour : black
Standards	CSA C22.2 No 8 1986 UL 1283 ed. 5 UL 1449 ed. 4
Ambient Operating	149 °F (65 °C)

Ordering and shipping details

Category	08466 - SURGE PROTECTION HWA
Discount Schedule	DE1B
GTIN	00785901630197
Nbr. of units in pkg.	5
Package weight(Lbs)	3.8999999999999999
Returnability	Y
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1743 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
California proposition 65	WARNING: This product can expose you to chemicals including:
----- Substance 1	DINP which is known to the State of California to cause cancer and
----- Substance 2	DIDP which is known to the State of California to cause birth defects or other reproductive harm.
----- More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------