

FAIRCHILD DIODES

DIODES

MILITARY QUALIFIED ZENER DIODES (BY ASCENDING V_Z) GLASS PACKAGE

Item	DEVICE NO.	V_Z V Nom	Tol. $\pm V_Z$ %	Z_Z Ω Max	@ I_Z mA	I_R μA Max	@ V	V_R V	T.C. %/°C Max	P_D mW $T_A=25^\circ C$	Package No.
1	1N747AJAN	3.6	5	22	20	3.0	1.0	-0.65	400	DO-7	
2	1N747AJANTX	3.6	5	22	20	3.0	1.0	-0.65	400	DO-7	
3	1N747AJANTXV	3.6	5	22	20	3.0	1.0	-0.65	400	DO-7	
4	1N748AJAN	3.9	5	20	20	2.0	1.0	-0.60	400	DO-7	
5	1N748AJANTX	3.9	5	20	20	2.0	1.0	-0.60	400	DO-7	
6	1N748AJANTXV	3.9	5	20	20	2.0	1.0	-0.60	400	DO-7	
7	1N749AJAN	4.3	5	18	20	2.0	1.0	-0.55	400	DO-7	
8	1N749AJANTX	4.3	5	18	20	2.0	1.0	-0.55	400	DO-7	
9	1N749AJANTXV	4.3	5	18	20	2.0	1.0	-0.55	400	DO-7	
10	1N750AJAN	4.7	5	16	20	5.0	1.5	-0.43	400	DO-7	
11	1N750AJANTX	4.7	5	16	20	5.0	1.5	-0.43	400	DO-7	
12	1N750AJANTXV	4.7	5	16	20	5.0	1.5	-0.43	400	DO-7	
13	1N751AJAN	5.1	5	14	20	5.0	2.0	± 0.30	400	DO-7	
14	1N751AJANTX	5.1	5	14	20	5.0	2.0	± 0.30	400	DO-7	
15	1N751AJANTXV	5.1	5	14	20	5.0	2.0	± 0.30	400	DO-7	
16	1N752AJAN	5.6	5	8.0	20	5.0	2.5	+0.32	400	DO-7	
17	1N752AJANTX	5.6	5	8.0	20	5.0	2.5	+0.32	400	DO-7	
18	1N752AJANTXV	5.6	5	8.0	20	5.0	2.5	+0.32	400	DO-7	
19	1N962BJAN	11	5	9.5	11.5	5.0	8.4	+0.73	400	DO-35	
20	1N962BJANTX	11	5	9.5	11.5	5.0	8.4	+0.73	400	DO-35	
21	1N962BJANTXV	11	5	9.5	11.5	5.0	8.4	+0.73	400	DO-35	
22	1N962B-1JAN	11	5	9.5	11.5	5.0	8.4	+0.73	400	DO-35	
23	1N962B-1JANTX	11	5	9.5	11.5	5.0	8.4	+0.73	400	DO-35	
24	1N962B-1JANTXV	11	5	9.5	11.5	5.0	8.4	+0.73	400	DO-35	
25	1N963BJAN	12	5	11.5	10.5	5.0	9.1	+0.76	400	DO-35	
26	1N963BJANTX	12	5	11.5	10.5	5.0	9.1	+0.76	400	DO-35	
27	1N963BJANTXV	12	5	11.5	10.5	5.0	9.1	+0.76	400	DO-35	
28	1N963B-1JAN	12	5	11.5	10.5	5.0	9.1	+0.76	400	DO-35	
29	1N963B-1JANTX	12	5	11.5	10.5	5.0	9.1	+0.76	400	DO-35	
30	1N963B-1JANTXV	12	5	11.5	10.5	5.0	9.1	+0.76	400	DO-35	
31	1N964BJAN	13	5	13	9.5	5.0	9.9	+0.79	400	DO-35	
32	1N964BJANTX	13	5	13	9.5	5.0	9.9	+0.79	400	DO-35	

2

Active

