

Detailed information for: CT-MFD.12

This page contains technical data sheet, documents library and links to offering related to this product. If you require any other information, please contact us using form located at the bottom of the page.

[Print...](#)
[Print to Pdf...](#)

Data Sheet Documentation

CT-MFD.12

General Information

Extended Product Type:	CT-MFD.12
Product ID:	15VR500020R0000
EAN:	4013614350634
Catalog Description:	CT-MFD.12 Time relay, multifunction 1c/o, 24-240VAC 24-48VDC

Long Description: The CT-MFD.12 is a multifunction electronic time relay from the CT-D timer range. It provides 7 timing functions with 7 time ranges from 0.05 s to 100 h. This time relay operates with a rated control supply voltage of 24 - 48 V DC / 24 - 240 V AC and has a 1 c/o (SPDT) output rated at 250 V / 4 A. A control input works with voltage-related (non-floating) triggering.

Categories

Products » Low Voltage Products and Systems » Control Products » Electronic Relays and Controls » Time Delay Relays



Ordering

EAN:	4013614350634
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	89 mm
Package Level 1 Depth / Length:	20 mm
Package Level 1 Height:	65 mm

Package Level 1 Gross Weight:	0.065 kg
Package Level 1 EAN:	4013614350634
Dimensions	
Product Net Width:	17.5 mm
Product Net Height:	70 mm
Product Net Depth / Length:	63 mm
Product Net Weight:	0.053 kg
Technical	
Timer Relay Type:	ON-Delay OFF-Delay Impulse ON Impulse OFF Flasher Starting with ON Flasher Starting with OFF Pulse Former
Time Range:	0.05 s - 100 h
Rated Control Supply Voltage (U_s):	24 ... 240 V AC 24 ... 48 V DC
Output:	1 c/o (SPDT) contact
Terminal Type:	Screw Terminals
Rated Operational Current AC-12 (230 V) 6 A (I_e):	
Rated Operational Current AC-15 (230 V) 3 A (I_e):	
Rated Operational Current DC-12 (24 V) 6 A (I_e):	
Rated Operational Current DC-13 (24 V) 2 A (I_e):	
Degree of Protection:	Housing IP50 Terminals IP20
Overvoltage Category:	III
Pollution Degree:	3
Short-Circuit Protective Devices:	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Connecting Capacity:	Flexible 1x 0.5 ... 2.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 1x 0.5 ... 4 mm ² Rigid 2x 0.5 ... 1.5 mm ²
Tightening Torque:	0.5 ... 0.8 N·m
Wire Stripping Length:	7 mm
Mounting Position:	Any
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards:	EN 50581 IEC/EN 61812-1 UL 508 CAN/CSA C22.2 No.14
Environmental	
Ambient Air Temperature:	Operation -20 ... +60 °C Storage -40 ... +85 °C

RoHS Status: Following EU Directive 2011/65/EU

Technical UL/CSA

Maximum Operating Voltage UL/CSA: Output Circuit 300 V AC

Contact Rating UL/CSA: C300

Connecting Capacity UL/CSA: Flexible 1x 18-14 AWG
Flexible 2x 18-16 AWG
Rigid 1x 20-12 AWG
Rigid 2x 20-16 AWG

Tightening Torque UL/CSA: 4.43 ... 7.08 in·lb

Certificates and Declarations (Document Number)

CB Certificate: [CB_DK-8574](#)

CCC Certificate: [CCC_2005010303153177](#)

cUL Certificate: [cUL508_E140448](#)

Data Sheet, Technical Information: [2CDC111154D0201](#)

Declaration of Conformity - CE: [1SVD981010-0001](#)

EAC Certificate: [EAC_RU_C-DE.ME77.B.02016](#)

Environmental Information: [1SAA981011-2402](#)

Instructions and Manuals: [1SVC500010M1000](#)

RMRS Certificate: [RMRS_1740021250](#)

RoHS Information: [1SVD981010-0001](#)

UL Certificate: [UL508_E140448](#)

Classifications

Object Classification Code: K

E-number: 4033001

ETIM 4: EC001439 - Timer relay

ETIM 5: EC001439 - Timer relay

ETIM 6: EC001439 - Timer relay

ETIM 7: EC001439 - Timer relay

eClass: 7.0 27371790

UNSPSC: 39121519

Contact information

What would you like to do?

I need more information

ABB Sales

Submit your inquiry

Country / region

United States of America

Name

Company

Your local ABB Sales Team

Name

Customer Support

E-Mail

Phone

Zip code

Your message

[→ Privacy policy](#)

Cancel

Send message

▲ Close