

| JEDEC No. | Type | Use | MAXIMUM RATINGS | | | | ELECTRICAL PARAMETERS | | | | | | Closest GE | Dwg. No. |
|-----------|------|--------|--------------------------|-------------------------------------|-------------------|-------------------|-----------------------------------|--------------------------|------------------------|---|-------|-----|------------|----------|
| | | | P _c mw @ 25°C | BV _{CE} BV _{CB} * | I _c ma | T _j °C | MIN. hfe-hFE* @ I _c ma | MIN. f _{hfb} mc | MIN. G _e db | MAX. I _{cc} (μa) @ V _{CB} | | | | |
| 2N2629 | PNP | | 150 | 32 | 100 | 110 | 10* | 1 | | | 10 | 12 | | |
| 2N2630 | PNP | Sw | 300 | 18 | 100 | 100 | 25* | 100 | | | 5 | 15 | | |
| 2N2631 | NPN | RF | | 80 | 1.5A | 200 | 8* | 200 | | 8.7 | .1 | 30 | | |
| 2N2632 | NPN | Pwr | | 90 | 5A | 175 | 40* | 1A | | | .1 | 60 | | |
| 2N2633 | NPN | Pwr | | 120 | 5A | 175 | 40* | 1A | | | .1 | 60 | | |
| 2N2634 | NPN | Pwr | | 150 | 5A | 175 | 40* | 1A | | | .1 | 60 | | |
| 2N2635 | PNP | Sw | 150 | 30 | 100 | 100 | 45* | 50 | | | 5 | 25 | | |
| 2N2636 | PNP | Pwr | 100W | 100 | 25A | 110 | 20* | 25A | | | 10ma | 100 | | |
| 2N2637 | PNP | Pwr | 100W | 100 | 25A | 110 | 20* | 25A | | | 10ma | 100 | | |
| 2N2638 | PNP | Pwr | 100W | 100 | 25A | 110 | 20* | 25A | | | 10ma | 100 | | |
| 2N2639 | NPN | Diff | 600 | 45 | 30 | 200 | 50* | 10μa | | | .010 | 45 | | |
| 2N2640 | NPN | Diff | 600 | 45 | 30 | 200 | 50* | 10μa | | | .010 | 45 | | |
| 2N2642 | NPN | Diff | 600 | 45 | 30 | 200 | 100* | 10μa | | | .010 | 45 | | |
| 2N2643 | NPN | Diff | 600 | 45 | 30 | 200 | 100* | 10μa | | | .010 | 45 | | |
| 2N2644 | | | | | | | | | | | | | | |
| 2N2645 | NPN | AF | 500 | 75 | | 200 | 100* | 150 | | | .010 | 60 | 2N956 | 16 |
| 2N2646 | PN | Si Uni | | | | | SEE G. E. SPECIFICATION SECTION | | | | | | 2N2646 | 29 |
| 2N2647 | PN | Si Uni | | | | | SEE G. E. SPECIFICATION SECTION | | | | | | 2N2647 | 29 |
| 2N2648 | PNP | Pwr | 5WC | 35 | 1A | 100 | 80* | 1A | | | 100 | 35 | | |
| 2N2649 | NPN | | 8.7WC | 65 | 1A | 200 | 10* | 500 | | | 500 | 65 | | |
| 2N2650 | NPN | | 8.7WC | 140 | 1A | 200 | 10* | 500 | | | 500 | 140 | | |
| 2N2651 | NPN | Sw | 1.2WC | 40 | 500 | 200 | 25* | 10 | | | .030 | 20 | | |
| 2N2652 | NPN | Diff | 600 | 100 | 500 | 200 | 35* | 100μa | | | .010 | 50 | 2N2652 | 21 |
| 2N2654 | PNP | | 100 | 25 | 10 | 75 | 25* | 1.0 | | 20 | 8.0 | 10 | | |
| 2N2655 | NPN | Pwr | 15WC | 100V | 500 | 200 | 30* | 200 | 4 | | 10 | 100 | | |
| 2N2656 | NPN | RF | 360 | 25 | 200 | 200 | 40* | .1 | | 10 | .5 | 15 | 2N918 | 17 |
| 2N2657 | NPN | Pwr | 1.25W | 80 | 5A | 200 | 40* | 1A | | | .1 | 60 | 2N657 | 5 |
| 2N2658 | NPN | Pwr | 1.25W | 100 | 5A | 200 | 40* | 1A | | | .1 | 60 | 2N657 | 5 |
| 2N2659 | | Pwr | | 50* | 3A | 100 | 30-90* | 500 | 30 | | 20 ma | 20 | | |
| 2N2660 | PNP | Pwr | 15W | 70* | 5A | 100 | 30-90* | 500 | 30 | | 20 ma | 20 | | |
| 2N2661 | PNP | Pwr | 15W | 90* | 3A | 100 | 30-90* | 500 | 30 | | 20 ma | 25 | | |
| 2N2662 | PNP | Pwr | 15W | 50* | 3A | 100 | 30-90* | 500 | 30 | | 20 ma | 25 | | |
| 2N2663 | PNP | Pwr | 15W | 70* | 3A | 100 | 30-90* | 500 | 30 | | 20 ma | 25 | | |
| 2N2664 | PNP | Pwr | 15W | 90* | 3A | 100 | 30-90* | 500 | 30 | | 20 ma | 25 | | |
| 2N2665 | PNP | Pwr | 15W | 50* | 3A | 100 | 50-150* | 500 | 30 | | 20 ma | 25 | | |
| 2N2666 | PNP | Pwr | 15W | 70* | 3A | 100 | 50-150* | 500 | 30 | | 20 ma | 25 | | |
| 2N2667 | PNP | Pwr | 15W | 90* | 3A | 100 | 50-150* | 500 | 30 | | 20 ma | 25 | | |
| 2N2668 | PNP | Pwr | 15W | 50* | 3A | 100 | 50-150* | 500 | 30 | | 20 ma | 25 | | |
| 2N2669 | PNP | Pwr | 15W | 70* | 3A | 100 | 50-150* | 500 | 30 | | 20 ma | 25 | | |
| 2N2670 | PNP | Pwr | 15W | 90* | 3A | 100 | 50-150* | 500 | 30 | | 20 ma | 25 | | |
| 2N2671 | PNP | AF | 100 | 25* | 10 | 75 | 40 | 1 | | 12 | 8 | 6 | | |
| 2N2672 | PNP | AF | 100 | 25* | 10 | 75 | 40 | 1 | | 40 | 8 | 6 | | |