

Part Number	V _{RRM} (V)	I _{FAV} @T _C		V _{FM} @I _{FM}		I _{FSM}		R _{θJC} (DC) (°C/W)	Notes	Fax on Demand Number	Case Outline Key
		(A)	(C)	(V)	(A)	50 Hz (A)	60Hz (A)				

Standard Recovery

Plastic Packages

											D-Pak	
8EWS08S	800	8	95	1.1	8	170	175	3.0	1	12	82108	H5
8EWS12S	1200	8	95	1.1	8	170	175	3.0	1	12	82108	
8EWS16S	1600	8	95	1.1	8	170	175	3.0	1	12	82108	
											D2Pak	
10ETS08S	800	10	105	1.1	10	170	175	2.5	1	12	82121	J4
10ETS12S	1200	10	105	1.1	10	170	175	2.5	1	12	82121	
10ETS16S	1600	10	105	1.1	10	170	175	2.5	1	12	82121	
20ETS08S	800	20	105	1.1	20	250	260	1.3	1	12	82102	J4
20ETS12S	1200	20	105	1.1	20	250	260	1.3	1	12	82102	
20ETS16S	1600	20	105	1.1	20	250	260	1.3	1	12	82102	
											PowIRTab	
85EPS08	800	85	95	1.1	85	1450	1500	0.35			82139	J21
85EPS12	1200	85	95	1.1	85	1450	1500	0.35			82139	
85EPS16	1600	85	95	1.1	85	1450	1500	0.35			82139	
											TO-220AC (2-pin)	
10ETS08	800	10	105	1.1	10	170	175	2.5		12	82120	J10A
10ETS12	1200	10	105	1.1	10	170	175	2.5		12	82120	
10ETS16	1600	10	105	1.1	10	170	175	2.5		12	82120	
20ETS08	800	20	105	1.1	20	250	260	1.3		12	82101	J10A
20ETS12	1200	20	105	1.1	20	250	260	1.3		12	82101	

NOTES: 1 Available on tape-and-reel 12 For Ifsm: 100% VRRM reapplied. Tj=Tj max.

