



**SPECIFICATIONS:**  
 RATING: 16V DC @ 2A  
 CONTACT RESISTANCE: 30m OHMS MAX  
 INSULATION RESISTANCE: 100M OHMS MIN @ 500V DC  
 WITHSTAND VOLTAGE: 500V AC FOR 1 MINUTE  
 LIFE: 5,000 CYCLES

NO.	DESCRIPTION	MATERIAL	QTY	FINISH
6	PIN(Ø2.0)	COPPER	1	NICKEL PLATED
5	COVER	PBT	1	BLACK COLOR
4	HOUSING	PBT	1	BLACK COLOR
3	BREAK TERMINAL	0.4T BRASS	1	SILVER PLATED
2	SLEEVE SPRING	0.2T TiCUR1-M-EH	1	SILVER PLATED
1	PIN TERMINAL	0.4T BRASS	1	SILVER PLATED



9615 SW Allen, Suite 103  
 Beaverton, OR 97005  
 Phone: (503) 643-4899  
 800-275-4899  
 Fax: (503) 372-1266  
 Website: www.cui.com

TITLE: **DC POWER JACK**

PART NO. PJ-012A UNITS: MM [INCHES]

DRAWN BY: Todd R. White APPROVED BY: SCALE: 3X

DatasheetLive