

QPL MIL-PRF-55342 Qualified Thin Film Resistor, Surface Mount Chip



FEATURES

- T-level (space) qualified
- Passes outgassing requirements of ASTM-E595 requirements
- TCR to ± 25 ppm/ $^{\circ}\text{C}$
- Tolerances to ± 0.1 %
- 100 % power conditioning

Thin Film MIL-PRF-55342 established reliability "T" level chip resistors feature a thin film resistor element and with all sputtered wraparound terminations that provide excellent adhesion and dimensional uniformity. They are ideal in applications requiring stringent performance requirements. Established reliability is assured through 100 % screening and extensive environmental testing for every lot that includes complete 100 % group A, power conditioning and group B lot testing performed for T-level product assurance.

TYPICAL PERFORMANCE

	ABSOLUTE
TCR	25
TOL.	0.1

STANDARD ELECTRICAL SPECIFICATIONS

TEST	SPECIFICATIONS	CONDITIONS
Material	Passivated nichrome	-
Resistance Range	100 Ω to 1.5 M Ω	-
TCR: Absolute	25 ppm/ $^{\circ}\text{C}$ (E), 50 ppm/ $^{\circ}\text{C}$ (H)	- 55 $^{\circ}\text{C}$ to + 125 $^{\circ}\text{C}$
Tolerance: Absolute	± 0.1 %	+ 25 $^{\circ}\text{C}$
Stability: Absolute	$\Delta R \pm 0.02$ %	2000 h at + 70 $^{\circ}\text{C}$
Voltage Coefficient	< 0.1 ppm/V	-
Working Voltage	40 V to 125 V	-
Operating Temperature Range	- 55 $^{\circ}\text{C}$ to + 125 $^{\circ}\text{C}$	-
Storage Temperature Range	- 55 $^{\circ}\text{C}$ to + 150 $^{\circ}\text{C}$	-
Noise	< - 25 dB	-
Thermal EMF	< 0.1 $\mu\text{V}/^{\circ}\text{C}$	-
Shelf Life Stability: Absolute	$\Delta R \pm 0.01$ %	1 year at + 25 $^{\circ}\text{C}$

COMPONENT RATINGS


CASE SIZE	MAX. WORKING VOLTAGE (V)	POWER RATING (mW)	RESISTANCE RANGE (Ω) BY CHARACTERISTICS TOLERANCE			
			E (0.1 %)	E (1 %, 2 %, 5 %)	H, K, M (0.1 %)	H, K, M (1 %, 2 %, 5 %)
M55342/02	40	125	49.9 to 301K	49.9 to 301K	20 to 301K	20 to 301K
M55342/03	75	200	49.9 to 649K	49.9 to 649K	10 to 649K	10 to 649K
M55342/04	125	150	49.9 to 1.69M	49.9 to 1.69M	10 to 1.69M	10 to 1.69M
M55342/06	50	150	49.9 to 475K	49.9 to 475K	10 to 475K	10 to 475K
D55342/07	100	250	49.9 to 1.5M	49.9 to 1.5M	10 to 1.5M	10 to 1.5M
M55342/10	75	500	49.9 to 1M	49.9 to 1M	49.9 to 1M	49.9 to 1M



E/H (T-Level) (Military M/D55342)

QPL MIL-PRF-55342 Qualified Thin Film Resistor, Vishay Thin Film
Surface Mount Chip

DIMENSIONS in inches



CASE SIZE	TERM.	L	W	T	D	E
M55342/02	B	0.055 ± 0.006	0.050 ± 0.003	0.012 to 0.033	0.010 ± 0.005	0.015 ± 0.005
M55342/03	B	0.105 ± 0.007	0.050 ± 0.003	0.015 to 0.033	0.015 ± 0.005	0.015 ± 0.005
M55342/04	B	0.155 ± 0.007	0.050 ± 0.003	0.015 to 0.033	0.015 ± 0.005	0.015 ± 0.005
M55342/06	B	0.080 ± 0.006	0.050 ± 0.003	0.015 to 0.033	0.016 ± 0.008	0.015 ± 0.005
D55342/07	B	0.126 ± 0.008	0.063 ± 0.005	0.015 to 0.033	$0.020 + 0.005/- 0.010$	$0.020 + 0.005/- 0.010$
M55342/10	B	0.105 ± 0.007	0.100 ± 0.005	0.015 to 0.033	0.015 ± 0.005	0.015 ± 0.005

ENVIRONMENTAL TESTS

ENVIRONMENTAL TEST	MIL-PRF-55342 LIMITS ($\Delta R \pm$)	VISHAY PERFORMANCE ($\Delta R \pm$)
Thermal Shock	0.10 %	0.02 %
Low Temperature Operation	0.10 %	0.03 %
Short Time Overload	0.10 %	0.05 %
High Temperature Exposure	0.10 %	0.01 %
Resistance to Bonding	0.20 %	0.01 %
Moisture Resistance	0.20 %	0.04 %
TCR	± 25 ppm/ $^{\circ}\text{C}$	< 15 ppm/ $^{\circ}\text{C}$
Life (2000 h at + 70 $^{\circ}\text{C}$)	0.05 %	0.02 %
Life (10 000 h at + 70 $^{\circ}\text{C}$)	2.00 %	0.04 %

MECHANICAL SPECIFICATIONS

Resistive Element	Passivated nichrome
Substrate Material	Alumina
Chip Terminations	Solder over nickel
Fused Solder	SN 63

E/H (T-Level) (Military M/D55342)



Vishay Thin Film QPL MIL-PRF-55342 Qualified Thin Film Resistor,
Surface Mount Chip

GLOBAL PART NUMBER INFORMATION																	
Global Part Numbering: M55342E06B1C00TTS																	
M	5	5	3	4	2	E	0	7	B	1	C	0	0	T	T	S	V
MODEL	TCR CHARACTERISTIC		CASE SIZE	TERMINATION	OHMIC VALUE			PRODUCT LEVEL DESIGNATOR		PACKAGING				VENDOR			
M55342 or D55342 (/07 size only)	E = 25 ppm/°C > 100 Ω H = 50 ppm/°C K = 100 ppm/°C (1) M = 300 ppm/°C (1)		02 = 0505 03 = 1005 04 = 1505 06 = 0705 07 = 1206 10 = 1010	B = Solderable	Three digits and a letter. Letter identifies tolerance, acts as multiplier and decimal locator. MULTIPLIER Tolerance 1 Ω 1 kΩ 1 MΩ 0.1 % A B C 1 % D E F 2 % G H T 5 % J K L 10 % M N P			T = Space level		BS = BULK 1 min., 1 mult WAFFLE PACK WS = WAFFLE 25 min., 1 mult WI = 25 min., 1 mult (item single lot date code) WP = 25 min., 1 mult (package unit single lot date code) TAPE AND REEL T0 = 100 min., 100 mult T1 = 1000 min., 1000 mult T3 = 300 min., 300 mult T5 = 500 min., 500 mult TF = Full reel TS = 100 min., 1 mult TI = 100 min., 1 mult (item single lot date code) TP = 100 min., 1 mult (package unit single lot date code)				V = Vishay Thin Film (1)			

Notes

⁽¹⁾ For K and M TCR ≥ 1 % tolerance add a V at end of part number to specify Vishay Thin Film vs. Dale Thick Film. E.g.: M55342K06B1F00TWSV

- Consult factory for additional case size qualification pending



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.