



Diode Pro Electron Series

Part No.	V _{rrm} (V) Min	I _{rrm} (mA) Max	V _{im} (V) Max	I _f (mA) @	t _{rr} (ns) Max	Package
BA128	75	100	1.0	50		DO-35
BA129	200	50	1.0	100		DO-35
BA130	30	100	1.0	10		DO-35
BA217	30	50	1.0	10		DO-35
BA218	50	50	1.0	10		DO-35
BA316	10	200	0.85	10	4.0	DO-35
BA317	30	200	0.85	10	4.0	DO-35
BA318	50	200	0.85	10	4.0	DO-35
BAS16	75	1000	1.1	50	6.0	TO-236
BAS19	100	100	1.0	100	50	TO-236
BAS20	150	100	1.0	100	50	TO-236
BAS21	200	100	1.0	100	50	TO-236
BAS29	90	100	0.84	50		TO-236
BAS31	90	100	0.84	50		TO-236
BAS35	90	100	0.84	50		TO-236
BAV17	25	100	1.0	100	50	DO-35
BAV18	60	100	1.0	100	50	DO-35
BAV19	120	100	1.0	100	50	DO-35
BAV20	200	100	1.0	100	50	DO-35
BAV21	250	100	1.0	100	50	DO-35
BAV70	70	5000	1.1	50	6.0	TO-236
BAV74	50	100	1.0	100	4.0	TO-236
BAV99	70	2500	1.1	50	6.0	TO-236
BAW56	70	2500	1.1	50	6.0	TO-236
BAW62	75	25	1.0	100	4.0	DO-35
BAW75	35	100	1.0	30	2.0	DO-35
BAW76	75	100	1.0	100	2.0	DO-35
BAX13	50	200	1.0	20	4.0	DO-35
BAX16	180	100	1.5	200	120	DO-35

Diode Pro Electron Series

7

Diode Pro Electron Series

T-03-01

Diode Pro Electron Series (Continued)

Part No.	V _{rrm} (V) Min	I _{rrm} (mA) Max	V _{rrm} (V) Max	Q	I _r (mA)	t _{rr} (ns) Max	Package
BAY19	120	100	1.0		100	50	DO-35
BAY71	50	100	1.0		20	2.0	DO-35
BAY72	125	100	1.0		100	50	DO-35
BAY73	125	1.0	1.0		200	3.0	DO-35
BAY74	50	100	1.1		300	4.0	DO-35
BAY80	150	100	1.0		150	50	DO-35
BAY82	15	100	1.0		20	0.75	DO-7