

4. SILICON PNP - LOW POWER TRANSISTORS

IN ORDER OF (1) MAX COLLECTOR DISSIPATION
(2) fab & (3) TYPE No.

LINE No.	TYPE No.	1 MAX. COLL. DISS. @25°C (W)	2 DERATE IN FREE AIR W/°C	T M E A M P	ABS MAX RATINGS @25°C				MAX. Icbo @Vcb	TYPICAL 'h' PARAMETERS			COMMON EMITTER			Cob (F)	STRUC-TURE	DWG Y200 s/a TO200	# L E O D E		
					Vcbo (V)	Vceo (V)	Vebo (V)	Ic (A)		Vcb (V)	le (A)	hfe	hoe (mhos)	hie (Ω)	hre (X.0001)						
1	CT764	400m	20M			20	20	5.0	500m	10n	5.0	150m	25	1	8.0p	↑	T092	A			
2	CT767	400m	20MΔ			40	30	5.0	10n	10n	100u	500	1	10p	↑	T092	A				
3	CT768	400m	20MΔ			60	60	5.0	10n	10n	100u	500	1	10p	↑	T092	A				
4	CT769	400m	20MΔ			40	30	5.0	10n	10n	100u	500	1	10p	↑	T092	A				
5	CT770	400m	20MΔ			60	60	5.0	10n	10n	100u	500	1	10p	↑	T092	A				
6	TP4413	400m	20M			40	30	5.0	500m	10n	1.0	10u	100	8.0p	↑	T092	A				
7	TP4413A	400m	20M			60	60	5.0	500m	10n	1.0	10u	100	8.0p	↑	T092	A				
8	TP4415	400m	20M			40	30	5.0	500m	10n	1.0	10u	40	8.0p	↑	T092	A				
9	TP4415A	400m	20M			60	60	5.0	500m	10n	1.0	10u	40	8.0p	↑	T092	A				
10	2N2595	400m	30MΔ	2.2m	SS	80	60	6.0	50m	25n	5.0	1.0m	15	Δ	1.2k	12k	10	6.0p	↑	T046	A
11	2N2598	400m	30MΔ	2.2m	SS	125	80	7.0	50m	25n	5.0	5.0m	20	Δ	1.2k	12k	10	6.0p	↑	T046	A
12	2N2604	400m	30MΔ	2.2m	SS	60	45	6.0	30m	10n	5.0	1.0m	60	Δ	1.0u	35	10	6.0p	↑	T046	A
13	JAN2N2604	400m	30MΔ	2.2m	SS	80	60	6.0	30m	10n	5.0	1.0m	60	Δ	40u	10k	10	6.0p	↑	T046	A
14	2N2605	400m	30MΔ	2.2m	SS	60	45	6.0	30m	10n	5.0	1.0m	150	Δ	1.0u	35	10	6.0p	↑	T046	A
15	JAN2N2605	400m	30MΔ	2.2m	SS	70	60	6.0	30m	10n	5.0	1.0m	150	Δ	60u	20k	10	6.0p	↑	T046	A
16	ST8035	400m	30MΔ			40	40	5	2.0	1.0u	5.0	1.0m	30					45p	PL	T018	A
17	2N2596	400m	40MΔ	2.2m	SS	80	60	6.0	50m	25n	5.0	1.0m	30	Δ	1.5k	12k	10	6.0p	↑	T046	A
18	2N2599	400m	40MΔ	2.2m	SS	125	80	7.0	50m	25n	5.0	5.0m	40	Δ	1.5k	12k	10	6.0p	↑	T046	A
19	2N2599A	400m	40MΔ	2.2m	SS	125	100	7.0	50m	25n	5.0	5.0m	40	Δ				6.0p	↑	T046	A
20	2N2602	400m	40MΔ	2.2m	SS	60	60	6.0	50m	25n	5.0	1.0m	36	Δ	1.0u	35	10	6.0p	↑	T046	A
21	2N3930	400m	40MΔ	2.3m	SJ	180	180	6.0	100m	10n	10	1.0m	80	Δ	25u	12k	10	6.0p	↑	T018	A
22	2N4017*	400m	40MΔ	2.2m	SJ	45	45	6.0	200m	10n	5.0	1.0m	250	Δ	50u	20k	10	6.0p	↑	R131a	PA
23	2N4018*	400m	40MΔ	2.2m	SJ	80	80	6.0	200m	10n	5.0	1.0m	100	Δ	40u	17k	10	6.0p	↑	R131a	PA
24	2N4019*	400m	40MΔ	2.2m	SJ	60	60	6.0	200m	10n	5.0	1.0m	100	Δ	50u	20k	10	6.0p	↑	R131a	PA
25	2N4021*	400m	40MΔ	2.3m	SJ	60	60	6.0	200m	0.1u	5.0	1.0m	100	Δ	40u	17k	10	6p	↑	R131c	PA
26	2N4024*	400m	40MΔ	2.3m	SJ	60	60	6.0	200m	0.1u	5.0	1.0m	100	Δ	40u	17k	10	6p	↑	R131c	PA
27	2N4357	400m	40MΔ	2.3m	SJ	240	240	6.0	100m	0.2u	10	1.0m	100	Δ	25u	12k	10	7p	↑	T018	A
28#	ZSA1091	400m	40MΔ	3.2m	SJ	300	300	-8	100m	100n	-100	-20m	30	↑				6.0p	PL	T092	B
29#	GES4248	400m	40M	4.0m	SJ	40	40	5.0	500m	10n	5.0	1.0m	50	↑				6.0p	PE	T092	A
30	ST8036	400m	40MΔ			40	40	5	2.0	1.0u	5.0	1.0m	60					45p	PE	T018	A
31	ST61000	400m	40MΔ	4.3m		40	35	40	100m	20n	6.0	1.0m	100	↑				7p	PE	T046	A
32	2N2605A	400m	45M	2.2m	SS	60	45	6.0	30m	2.0n	5.0	1.0m	600	↑	1.0u	35	10	6.0p	↑	T046	A
33	2N3547	400m	45MΔ	2.2m	SS	60	60	6.0	100m	25n	5.0	1.0m	100	↑	1.0u	35	10	8.0p	↑	T018	A
34	2N721	400m	50MΔ	2.7m	SJ	50	35	5.0	1.0u	5.0	5.0	1.0m	15	Δ	1.0u	35	8.0	45p	↑	T018	A
35	2N721A	400m	50MΔ	2.2m	SJ	50	35	5.0	100n	10n	5.0	1.0m	15	↑	5.0u	10	8.0	40p	↑	T018	A
36	2N2590	400m	50MΔ	2.2m	SJ	100	60	7.0	50m	25n	5.0	5.0m	40	Δ	1.5u	10		15p	↑	T046	A
37	2N3341†	400m	50MΔ	2.7m	SA	30	20	5.0	30m	0.1u	1.0	0.1m	40	↑				6p	↑	T046	A
38	2N4020*	400m	50MΔ	2.3m	SJ	45	45	6.0	200m	0.1u	5.0	1.0m	250	Δ	50u	20k	10	6p	↑	R131c	PA
39	2N4022*	400m	50MΔ	2.3m	SJ	60	60	6.0	200m	0.1u	5.0	1.0m	250	Δ	50u	20k	10	6p	↑	R131c	PA
40	2N4023*	400m	50MΔ	2.3m	SJ	45	45	6.0	200m	0.1u	5.0	1.0m	250	Δ	50u	20k	10	6p	↑	R131c	PA
41	2N4025*	400m	50MΔ	2.3m	SJ	60	60	6.0	200m	0.1u	5.0	1.0m	250	Δ	50u	20k	10	6p	↑	R131c	PA
42#	BC393†	400m	50MΔ			180	180	6.0	100m	1.0u	10	1.0m	50	↑				7.0p	↑	T018	A
43	2N722	400m	60MΔ	2.6m	SJ	50	35	5.0	50m	1.0u	5.0	1.0m	25	Δ	1.0u	35	8.0	45p	↑	T018	A
44	2N2597	400m	60MΔ	2.2m	SS	80	60	6.0	50m	25n	5.0	1.0m	60	Δ	1.8k	12k	10	6.0p	↑	T046	A
45	2N2600	400m	60MΔ	2.2m	SS	125	80	7.0	50m	25n	5.0	5.0m	60	Δ	1.8k	12k	10	6.0p	↑	T046	A
46	2N2600A	400m	60MΔ	2.2m	SS	125	100	7.0	50m	25n	5.0	5.0m	80	Δ				6.0p	↑	T046	A
47	2N2603	400m	60MΔ	2.2m	SS	60	60	6.0	50m	25n	5.0	1.0m	76	Δ	1.0u	35	10	6.0p	↑	T046	A
48	2N3548	400m	60MΔ	2.2m	SS	60	45	6.0	100m	10n	5.0	1.0m	100	↑	1.0u	35	10	8.0p	↑	T018	A
49	2N3549	400m	60MΔ	2.2m	SS	60	60	6.0	100m	10n	5.0	1.0m	100	↑	1.0u	35	10	8.0p	↑	T018	A
50	2N3550	400m	60MΔ	2.2m	SS	60	45	10	100m	1.0n	5.0	1.0m	200	↑	1.0u	35	10	8.0p	↑	T018	A
51	2N3726	400m	60MΔ	2.2m	SJ	45	45	5.0	300m	10n	10	1.0m	135	Δ	80u	11k	15	8.0p	↑	R131c	PA
52	2N3727	400m	60MΔ	2.2m	SJ	45	45	5.0	300m	10n	10	1.0m	135	Δ	80u	11k	15	8.0p	↑	R131c	PA
53#	BFW43	400m	60.M	2.3m	SJ	150	150	6.0	0.1u	10	10	1.0m	40	↑				7p	PE	T018	A
54#	BFX90	400m	60.M	2.3m	SJ	180	180	6.0	0.1u	10	10	1.0m	170	↑				5.0p	PE	T018	A
55#	FP50201	400m	60MΔ	4.0m	↑	30	20	5.0	200m	10n	1.0	50m	132	↑				12p	PE	T092	A
56	TD509*	400m	60M			25	20	5.0	500m	10n	5.0	10u	15				8.0p	↑	T018	PA	
57	TD510*	400m	60M			25	20	5.0	500m	10n	5.0	10u	20				8.0p	↑	T018	PA	
58	TD511*	400m	60M			25	20	5.0	500m	10n	5.0	10u	20				8.0p	↑	T018	PA	
59	TD512*	400m	60M			25	20	5.0	500m	10n	5.0	10u	40				8.0p	↑	T018	PA	
60	TD513*	400m	60M			25	20	5.0	500m	10n	5.0	10u	40				8.0p	↑	T018	PA	
61	TD514*	400m	60M			25	20	5.0	500m	10n	5.0	10u	40				8.0p	↑	T018	PA	
62	2N2591	400m	70MΔ	2.2m	SS	100	60	7.0	50m	25n	5.0	5.0m	70	Δ	1.5u	10		15p	↑	T046	A
63	2N3579	400m	80MΔ	2.2m	SS	60	60	6.0	30m	50n	5.0	1.0m	120	↑	1.0u	35	10	6.0p	↑	T046	A
64	2N3580	400m	80MΔ	2.2m	SS	60	60	6.0	30m	50n	5.0	1.0m	240	↑	1.0u	35	10	6.0p	↑	T046	A
65#	2SA493G	400m	80M	4.0m	↑	50	50	5.0	150m	100n	6.0	2.0m	120	↑				6.0p	↑	T092	B
66#	2SA1015	400m	80MΔ	4.0m	↑	50	50	5.0	150m	100n	6.0	2.0m	70	↑				4.0p	↑	T092	B
67	O801	400m	80MΔ			50	45	5.0	500m	1.0	10	100m	100	↑				15p	↑	T0105	B
68	O802	400m	80MΔ			100	80	5.0	500m	1.0	10	100m	40	↑				15p	↑	T0105	B
69	O803	400m	80MΔ			80	60	5.0	500m	1.0	10	100m	100	↑				15p	↑	T0105	B
70	2N2592	400m	90MΔ	2.2m	SS	100	60	7.0	50m	25n	5.0	5.0m	115	Δ	1.5u	10		15p	↑	T046	A
71#	2SA1025	400m	90M	4.0m	↑	60	60	5.0	100m	0.1u	12	2.0m	800	↑				3.5p	↑	T092	B
72#	2SA1081	400m	90M	4.0m	↑	90	90	5.0	100m	0.1u	12	2.0m	800	↑				3.5p	↑	T092	B
73#	2SA																				