



Browse

▶ [Quartz Crystal Units](#)

▶ [Monolithic Crystal Filter](#)

▶ [Oscillator](#)

Choice

Monolithic Crystal Filter

SPECIFICATION

Model	Centre Frequency (MHZ)	Pole	Insertion Loss(dB)	Passband Ripple (dB)	3dB Passband Width (kHz)	Attenuation Bandwidth(KHz)					Useless Signal (dB)	Attenuation Max (dB)	Terminating Impedance (k Ω /PF)	Dimensions (mm)
						18dB	20dB	40dB	60dB	80dB				
21.4M20A	21.4	2	2.0	0.5	+/-10	+/-32						1.5	UM-1	
21.4M20B	21.4	4	2.0	2.0	+/-10			+/-32				1.5	UM-1x2	
21.4M20C	21.4	6	3.0	2.0	+/-10			+/-30				1.5	Fig.7(a)	
21.6M7.5A	21.6	2	2.0	1.0	+/-3.75	+/-15						0.9/5	UM-1	
21.6M7.5B	21.6	4	2.0	1.0	+/-3.75			+/-15				0.9	UM-1x2	
21.6M15A	21.6	2	1.5	0.5	+/-7.5	+/-25						1.6	UM-1	
21.6M15B	21.6	4	2.0	1.0	+/-7.5			+/-25				1.6	UM-1x2	
30M10A	30	2	2.0	0.5	+/-6.0	+/-25						1.5	UM-1	
30M15B	30	4	2.0	1.5	+/-7.5			+/-25				1.5	UM-1x2	
45M15A	45	2	2.0	1.0	+/-7.5	+/-28						1.0	UM-1	
45M15B	45	4	3.0	1.0	+/-7.5			30dB +/-25				1.0	UM-1x2	
45M20B	45	4	3.0	1.5	+/-10			35dB +/-40				1.0	UM-1x2	
45M15AF*	45	2	2.0	1.0	+/-7.5	+/-25						4.0	UM-1	
45M15BF*	45	4	2.0	2.0	+/-7.5			+/-25				4.0	UM-1x2	
45M20BF*	45	4	3.0	2.5	+/-10			+/-28				5.0	UM-1x2	

58M15BF*	58	4	3.0	2.0	+/-7.5			+/-25					5.0	UM-1x2
75M15AF*	75	2	4.0	2.0	+/-7.5	+/-28							4.0	UM-1

[PREVIOUS PAGE](#) | [NEXT PAGE](#)

[About us](#) | [Product](#) | [Contact us](#)

Copyright (C) 2000 BEIJING YUNIKE ELECTRONIC COMPONENTS Co. Ltd. All Rights Reserved