



GENERAL PURPOSE AMPS

N-Channel JFETs

Type No.	Case Style	BV _{GSS} * BV _{GDO} (V) @ I _G (μA)		I _{GSS} (nA) @ V _{DG} (V)		V _p (V) @ V _{DS} (V)		I _{DSS} (mA) @ V _{DS} (V)		G _{fs} (mmho) @ V _{DS} (V)		G _{oss} (μmho) @ V _{DS} (V)		C _{iss} (pF) @ V _{DS} (V)		C _{rss} (pF) @ V _{DS} (V)		e _n (NV/√Hz) @ Freq (Hz)	Process No.	Pkg. No.							
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max				Min	Max					
2N3369	TO-18	40	1	5	30	6.5	20	1000	0.5	2.5	30	0.6	2.5	30	30	30	20	8	0	3	30	0	52	02			
2N3370	TO-18	40	1	5	30	3.2	20	1000	0.1	0.6	30	0.3	2.5	30	15	30	20	8	0	3	30	0	52	02			
2N3458	TO-18	50	1	0.25	30	7.8	20	1000	3	15	20	2.5	10	20	35	30	18	0	-10	5	30	0	225	20	52	02	
2N3459	TO-18	50	1	0.25	30	3.4	20	1000	0.8	4	20	1.5	6	20	20	30	18	0	-6	5	30	0	155	20	52	02	
2N3460	TO-18	50	1	0.25	30	1.8	20	1000	0.2	1	20	0.8	4.5	20	5	30	18	0	-4	5	30	0	155	20	52	02	
2N3684	TO-72	50	1	0.1	30	2	5	20	1	2.5	7.5	20	2	3	20	50	20	4	20	0	1.2	20	0	150	100	52	25
2N3685	TO-72	50	1	0.1	30	1	3.5	20	1	1	3	20	1.5	2.5	20	25	20	4	20	0	1.2	20	0	150	100	52	25
2N3686	TO-72	50	1	0.1	30	0.6	2	20	1	0.4	1.2	20	1	2	20	10	20	4	20	0	1.2	20	0	150	100	52	25
2N3687	TO-72	50	1	0.1	30	0.3	1.2	20	1	0.1	0.5	20	0.5	1.5	20	5	20	4	20	0	1.2	20	0	150	100	52	25
2N3821	TO-72	50	1	0.1	30	4	15	0.5	0.5	2.5	15	1.5	4.5	15	10	15	6	15	0	3	15	0	200	10	55	25	
2N3822	TO-72	50	1	0.1	30	6	15	0.5	2	10	15	3	6.5	15	20	15	6	15	0	3	15	0	200	10	55	25	
2N3967	TO-72	30	1	0.1	20	2	5	20	1	2.5	10	20	2.5	20	35	20*	5	20	†	1.3	20	■	84	100	55	25	
2N3967A	TO-72	30	1	0.1	20	2	5	20	1	2.5	10	20	2.5	20	35	20*	5	20	†	1.3	20	■	160	10	55	25	
2N3968	TO-72	30	1	0.1	20	3	20	1	1	5	20	2	20	15	20**	5	20	**	1.3	20	†	84	100	55	25		
2N3968A	TO-72	30	1	0.1	20	3	20	1	1	5	20	2	20	15	20**	5	20	**	1.3	20	†	160	10	55	25		
2N3969	TO-72	30	1	0.1	20	1.7	20	1	0.4	2	20	1.3	20	5	20††	5	20	††	1.3	20	†	84	100	55	25		
2N3969A	TO-72	30	1	0.1	20	1.7	20	1	0.4	2	20	1.3	20	5	20††	5	20	††	1.3	20	†	160	10	55	25		
2N4220	TO-72	30	10	0.1	15	4	15	0.1	0.5	3	15	1	4	15	10	15	6	15	0	2	15	0	55	25	55	25	
2N4220A	TO-72	30	10	0.1	15	4	15	0.1	0.5	3	15	1	4	15	10	15	6	15	0	2	15	0	115	100	55	25	
2N4221	TO-72	30	10	0.1	15	6	15	0.1	2	6	15	2	5	15	20	15	6	15	0	2	15	0	55	25	55	25	
2N4221A	TO-72	30	10	0.1	15	6	15	0.1	2	6	15	2	5	15	20	15	6	15	0	2	15	0	115	100	55	25	
2N4222	TO-72	30	10	0.1	15	8	15	0.1	5	15	15	2.5	6	15	40	15	6	15	0	2	15	0	55	25	55	25	
2N4222A	TO-72	30	10	0.1	15	8	15	0.1	5	15	15	2.5	6	15	40	15	6	15	0	2	15	0	115	100	55	25	
2N4338	TO-18	50	1	0.1	30	0.3	1	15	100	0.2	0.6	15	0.6	1.8	15	5	15	7	15	0	3	15	0	68	1000	52	02
2N4339	TO-18	50	1	0.1	30	0.6	1.8	15	100	0.5	1.5	15	0.8	2.4	15	15	15	7	15	0	3	15	0	68	1000	52	02
2N4340	TO-18	50	1	0.1	30	1	3	15	100	1.2	3.6	15	1.3	3	15	30	15	7	15	0	3	15	0	68	1000	52	02
2N4341	TO-18	50	1	0.1	30	2	6	15	100	3	9	15	2	4	15	60	15	7	15	0	3	15	0	68	1000	55	02
2N5103	TO-72	25	10	0.1	15	0.5	4	15	1	1	8	15	2	8	15	100	15	5	15	0	1	15	0	100	10	50	25
2N5104	TO-72	25	1	0.1	15	0.5	4	15	1	2	6	15	3.5	7.5	15	100	15	5	15	0	1	15	0	50	10	50	25

■ I_D = 1 mA; † I_D = 500 μA; †† I_D = 40 μA; ** I_D = 100 μA; ††† I_D = 250 μA.

t = typical value.

37