


DIM	MIN	MAX
A	5,24	5,84
B	4,52	4,95
C	4,31	5,33
D	0,40	0,53
E	-	0,76
F	1,14	1,39
G	2,28	2,97
H	0,91	1,17
J	0,71	1,22
K	12,7	-
L	12 DEG	48 DEG

ALL DIMENSIONS ARE IN M.M.

Pin Configuration Available in TO-72



CDIL Code Style	PIN 1	PIN 2	PIN 3	PIN 4
TO-72	Emitter	Base	Collector	Case
TO-72-1	Base	Emitter	Collector	Case
TO-72-2	Source	Drain	Gate	Case

Datasheet.Live

**TO-72 Metal-Can Package Transistors (NPN)**

Maximum Ratings						Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)																	
Type No.	V <sub>CBO</sub> (V) Min	V <sub>CEO</sub> (V) Min	V <sub>EBO</sub> (V) Min	P <sub>D</sub> (W) @ Ta=25°C	I <sub>C</sub> (A)	I <sub>CBO</sub> (μA) Max	V <sub>CE</sub> (V) @ I <sub>C</sub>	I <sub>CES</sub> Max	V <sub>CE</sub>	h <sub>FE</sub> Min	h <sub>FE</sub> @ I <sub>C</sub> & V <sub>CE</sub> (mA) Max	V <sub>CE(SAT)</sub> (V) & V <sub>BE(SAT)</sub> (V) @ I <sub>C</sub> (mA)	I <sub>C</sub> (mA)	f <sub>T</sub> (MHz) @ I <sub>C</sub> (mA)	NF (dB) @ Freq (MHz)	C <sub>re</sub> (pF) Max	CDIL Case Style						
2N3933	40	30	2.5	0.2		0.01	15			60	200	2	8	0.55	750	1600	2	4	200	TO-72			
2N5179	20	12	2.5	0.2	0.05	0.02	15			25	250	3	1	0.4	1	10	1	900	2000	5	4.5	200	TO-72
2N917	30	15	3	0.2	0.05	1	15			20	200	3	1	0.4	1	10	2	6		4			TO-72
2N918	30	15	3	0.2	0.05	0.01	15			20		3	1	0.4	1	10	1.7	600		4			TO-72
2SC2570	25	12	3	0.6	0.07	0.1	15			40	200	20	10				0.9		5000	20	3	1000	TO-72-1
2SC568	30	15	3	0.2	0.02	0.1	15			30	250	2	6				1	2		5	5		TO-72
BF115	50	30	5	0.145	0.03					48	167	1	10						230	1			TO-72
BF167	40	30	4	0.15	0.03			0.05	10	30		4	10										TO-72-1
BF173	40	25	4	0.2	0.03					15	20	2	10						550	5	3.5	36	TO-72
BF180	30	20	3	0.15	0.02	0.1	20			13		2	10										TO-72
BF181	30	20	3	0.15	0.02	0.1	20			6		12	7										TO-72
BF182	25	20	3	0.15	0.02	0.4	15			10		2	10						650	2	3.3	0.33	TO-72-1
BF184	30	20	5	0.145	0.03					67	220	1	10	0.7	0.74	1		200		1	2	0.9	TO-72-1
BF185	30	20	5	0.145	0.03					36	125	1	10	0.7	0.74	1		200	260	1	2	0.9	TO-72-1
BF200	30	20	3	0.15	0.02	0.1	40			15		3	10										TO-72